

50Ω Semi-rigid Coaxial Cable	.085SS-W-P-50		
DIMENSIONS			
Center Conductor Diameter			
(inch)	0.0201±0.0005		
(mm)	0.51 ± 0.0127		
Dielectric Diameter			
(inch)	0.0654±0.001		
(mm)	1.66 ±0.0254		
Outer Conductor Diameter			
(inch)	0.858±0.001		
(mm)	2.16 ±0.0254		
MATERIAL SPECIFICATIONS			
Outer Conductor	Stainless Steel		
Dielectric	PTFE		
Center Conductor	SPCW		
ELECTRICAL CHARACTERISTICS			
Impedance	50±2.5		
Capacitance (Nominal)			
(pF/ft)	29.0		
(pF/m)	95.1		
Corona Extinction Voltage			
(VRMS 60Hz)	1500		
Voltage Withstanding			
(VRMS 60Hz)	5000		
Cut off Frequency (GHz)	61		
Typical Attenuation	Attenuation		Power
Average Power (Watts CW) at 20°C and Sea Level	dB/ 100Ft	dB/ 100M	
0.5GHz	31.2	102.3	142.8
1GHz	44.4	145.3	100.6
5GHz	101.6	333.2	44.2
10GHz	146.1	479.2	30.9
20GHz	211.4	693.4	21.4
MECHANICAL CHARACTERISTICS			
Max. Operating Temperature (°C)	200		
Min. Inside Bend Radius			
(inch)	0.125		
(mm)	3.18		
Weight			
(g/Ft)	6.1		
(g/M)	20		

This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.