

High Impedance Semi-Rigid Cable	.141CU-W-P-75		
DIMENSIONS			
Center Conductor Diameter			
(inch)	0.0201±0.0005		
(mm)	0.51 ± 0.0127		
Dielectric Diameter			
(inch)	0.1175±0.001		
(mm)	2.98 ±0 .0254		
Outer Conductor Diameter			
(inch)	0.141±0.001		
(mm)	3.58 ±0.0254		
MATERIAL SPECIFICATIONS			
Outer Conductor	BARE COPPER		
Dielectric	PTFE		
Center Conductor	SPCW		
ELECTRICAL CHARACTERISTICS			
Impedance	75±1		
Capacitance (Nominal)			
(pF/ft)	19.3		
(pF/m)	63.5		
Corona Extinction Voltage			
(VRMS 60Hz)	2000		
Voltage Withstanding			
(VRMS 60Hz)	5000		
Cut off Frequency (GHz)	38		
Typical Attenuation	Attenuation		Power
Average Power (Watts CW) at 20°C and Sea Level	dB/ 100Ft	dB/ 100M	
0.5GHz	8.4	27.6	549.0
1GHz	12.1	39.7	382.2
5GHz	29.4	96.4	160.6
10GHz	44.1	144.7	108.6
20GHz	67.2	220.4	72.4
MECHANICAL CHARACTERISTICS			
Max. Operating Temperature (°C)	125		
Min. Inside Bend Radius			
(inch)	0.075		
(mm)	1.91		
Weight			
(g/Ft)	13.5		
(g/M)	44.3		

This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.