

50Ω Semi-rigid Coaxial Cable	.141TIN-C-L-50		
DIMENSIONS			
Center Conductor Diameter			
(inch)	0.0403±0.0001		
(mm)	1.024 ± 0.025		
Dielectric Diameter			
(inch)	0.1175±0.002		
(mm)	2.984 ±0.0508		
Outer Conductor Diameter			
(inch)	0.141±0.002		
(mm)	3.581±0.0508		
MATERIAL SPECIFICATIONS			
Outer Conductor	Tin Plated Copper		
Dielectric	Low Density PTFE		
Center Conductor	SPC		
ELECTRICAL CHARACTERISTICS			
Impedance	50±2		
Capacitance (Nominal)			
(pF/ft)	26.6		
(pF/m)	87.3		
Corona Extinction Voltage			
(VRMS 60Hz)	1900		
Voltage Withstanding			
(VRMS 60Hz)	5000		
Cut off Frequency (GHz)	36		
Typical Attenuation	Attenuation		Power
Average Power (Watts CW) at 20°C and Sea Level	dB/ 100Ft	dB/ 100M	
0.5GHz	7	23	656
1GHz	10	32.8	460
5GHz	23	75.4	199
10GHz	33.3	109.2	137
20GHz	48.5	159	93
26.5GHz	56.7	186	80
MECHANICAL CHARACTERISTICS			
Max. Operating Temperature (°C)	250		
Min. Inside Bend Radius			
(inch)	0.500		
(mm)	12.7		
Weight			
(g/Ft)	14.8		
(g/M)	48.5		

This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.