JYEBAO

www.jyebao.com.tw

2.4mm Jack End Launch 2.4-84EL-07/12 50Ω With .007 Inch Board Pin 20,27 [.798] [.500] 9.32 6.35 2-LOCK [.367] [.250] WASHER 2-M2X0.4P M7X0.75P [.375] 9.53 Α 4.77 TRANSITION BLOCK GROUNDING B-[.250] [.167] [.188] PLATE 9.5 SQ. 9.53 THREADED. [.374 SQ.] [.375] CIRCUIT TRACE Ø0.99 0.76 [ø.039] Ø0.18 [.030] Ø0.31 [ø.012] Ø0.18 [ø.007] LAUNCH PIN-EQ. EQ. SUBSTRATE VIEW A **DETAIL B** [.375] SUBSTRATE GROUND CONDUCTOR NOTE: LOW VSWR; DIRECT MATCH TO SOUTHWEST MICROWAVE P/N 1492-03A-5

Parts	Material	Plating (Micro-inch)
Lock Washer	Stainless Steel	Passivated
Screw	Stainless Steel	Passivated
Launch Pin	Beryllium Copper	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20
Insulator (for launch pin)	PTFE	
Grounding Plate	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50
Clamping Plate	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50
Transition Block	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50
Contact Pin	Beryllium Copper	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20
Insulator	PEI	
Body	Stainless Steel	Passivated

This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.