JYEBAO

www.jyebao.com.tw

2.4mm Jack End Launch 2.4-84EL-10/20 50Ω With .010 inch board pin 20.27 [.798] [.500] 9.32 6.35 2-LOCK [.367] [.250] WASHER 2-M2X0.4P M7X0.75P [.375] 9.53 Α 4.77 TRANSITION BLOCK GROUNDING B [.250] [.167] [.188] PLATE 9.5 SQ. 9.53 THREADED. [.374 SQ.] [.375] CIRCUIT TRACE Ø1.61 1.27 [.050] [ø.063] Ø0.5 [ø.020] Ø0.25 [Ø.010] LAUNCH PIN-EQ. EQ. SUBSTRATE VIEW A 9,53 [,375] **DETAIL B** SUBSTRATE GROUND CONDUCTOR NOTE: LOW VSWR; DIRECT MATCH TO SOUTHWEST MICROWAVE P/N 1492-02A-5

Parts	Material	Plating (Micro-inch)
Lock Washer	Stainless Steel	Passivated
Screw	Stainless Steel	Passivated
Launch Pin	Beryllium Copper	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20
Insulator (for launch pin)	PTFE	
Grounding Plate	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50
Clamping Plate	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50
Transition Block	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50
Contact Pin	Beryllium Copper	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20
Insulator	PEI	
Body	Stainless Steel	Passivated

This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.