


NO.	COMPONENTS	IMPEDANCE
1	SMA MALE RIGHT ANGLE	50 OHM
2	.085" TIN PLATED SEMI-RIGID CABLE (TIN PLATED RG405)	50 OHM
3	N FEMALE FOR BULKHEAD	50 OHM

REVISION			
REV.	DESCRIPTION	DATE	APPROVED
-	INITIAL RELEASE	2011/03/15	

SMA MALE  
RIGHT ANGLE



2

3


N FEMALE  
FOR BULKHEAD

IP67 (MATED)


5/8-24UNEF-2A

1.9 [7.48] HEX

GASKET



1.35  
[5.31]



MOUNTING HOLE

JYE BAO P/N	L CM (INCH)	L1 FT (MM)
A39N85-85T-15	15 (5.906)	0.436 (133.0)
A39N85-85T-30	30 (11.811)	0.928 (283.0)
A39N85-85T-50	50 (19.685)	1.585 (483.0)
A39N85-85T-100	100 (39.370)	3.225 (983.0)
A39N85-85T-150	150 (59.055)	4.865 (1483.0)
A39N85-85T-200	200 (78.740)	6.506 (1983.0)
A39N85-85T-XXX	CUSTOM LENGTH IN CM	- - -

NO.	PARTS NO.	DESCRIPTION	QTY	U/M
3	N8305P-0085	N JACK	1	EA
2	.085TIN-W-P-50	CABLE	L1 (SEE TABLE)	FT
1	SMA3300-9085	SMA PLUG R/A	1	EA

DIMENSION ARE MILLIMETERS UNLESS OTHERWISE SPECIFIED TOLERANCES ( UNIT: MM )
LENGTH TOLERANCE IS ±1.5% OR ±10MM, WHICHEVER IS GREATER.

STANDARD	REV -	UNIT CM(INCH)
APPROVED	DATE	
CHECKED	DATE	
DRAWING Albert	DATE	

<b>JYE BAO CO., LTD.</b>	
TAIPEI TAIWAN	
DESCRIPTION	CABLE ASSEMBLY SMA PLUG R/A TO N JACK FOR BULKHEAD
JYE BAO DRAWING NO.	A39N85-85T-XXX