


| NO. | COMPONENTS   | IMPEDANCE |
|-----|--|-----------|
| 1   | SMA REVERSE POLARITY MALE                            | 50 OHM    |
| 2   | .141" TIN PLATED SEMI-RIGID CABLE (TIN PLATED RG402) | 50 OHM    |
| 3   | SMB MALE RIGHT ANGLE                                 | 50 OHM    |



| JYE BAO P/N     | L<br>CM (INCH)         |
|-----------------|------------------------|
| A60S39-141T-15  | 15 (5.906)             |
| A60S39-141T-30  | 30 (11.811)            |
| A60S39-141T-50  | 50 (19.685)            |
| A60S39-141T-100 | 100 (39.370)           |
| A60S39-141T-150 | 150 (59.055)           |
| A60S39-141T-200 | 200 (78.740)           |
| A60S39-141T-XXX | CUSTOM<br>LENGTH IN CM |

|  |   |
|--|---|
| <b>LENGTH TOLERANCE IS ±1.5% OR ±10MM, WHICHEVER IS GREATER.</b> | <b>JYE BAO CO., LTD.</b><br>TAIPEI TAIWAN                                 |
|  | <small>DESCRIPTION</small><br>CABLE ASSEMBLY SMA R/P PLUG TO SMB PLUG R/A |
|  | <small>JYE BAO DRAWING NO.</small><br>A60S39-141T-XXX                     |