

AD-B8FME3	BNC Jack To FME Plug 2GHz VSWR 1.2	50Ω												
<table border="1"> <thead> <tr> <th>Parts</th> <th>Material</th> <th>Plating (Micro-inch)</th> </tr> </thead> <tbody> <tr> <td>Contact Pin</td> <td>Beryllium Copper</td> <td>Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20</td> </tr> <tr> <td>Insulator</td> <td>Teflon &amp; POM</td> <td></td> </tr> <tr> <td>Body</td> <td>Brass</td> <td>Tin-Zinc-Copper-Alloy 100 Over Copper 50</td> </tr> </tbody> </table>	Parts	Material	Plating (Micro-inch)	Contact Pin	Beryllium Copper	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20	Insulator	Teflon & POM		Body	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50		
Parts	Material	Plating (Micro-inch)												
Contact Pin	Beryllium Copper	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20												
Insulator	Teflon & POM													
Body	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50												
<p>Weight:</p>														

This part number complies with RoHS.  
 Notice: JYEBAO reserves the right to make modifications deemed appropriate.

AD-B8FME3		BNC Jack To FME Plug 2GHz VSWR 1.2	
<div style="border: 1px solid black; padding: 2px;">Interface</div>		BNC	FME
Standard		MIL-STD-348B	Jyebao FME series
<div style="border: 1px solid black; padding: 2px;">Electrical Data</div>			
Impedance	50Ω		
Frequency Range	DC To 2GHz		
VSWR	≤ 1.2 (DC To 2GHz)		
Insertion Loss	≤ 0.05 x √f(GHz) dB		
Insulation Resistance	≥ 5000MΩ		
Dielectric Withstanding Voltage (at sea level)	1000 V rms		
Working Voltage (at sea level)	500 V rms		
<div style="border: 1px solid black; padding: 2px;">Mechanical Data</div>			
	BNC	FME	
Recommended Coupling Nut Torque	0.6 to 2.5 in-lbs	≤ 17 in-lbs	
Contact Captivation-axial	≥ 6.1 lbs	NA	
Durability (mating)	≥ 500	≥ 300	
<div style="border: 1px solid black; padding: 2px;">Environmental Data</div>			
Temperature Range	-40°C to +90°C		
Thermal Shock	MIL-STD-202, Method 107, Condition B		
Moisture Resistance	MIL-STD-202, Method 206		
Corrosion	MIL-STD-202, Method 101, Condition B		
RoHS	Compliant		

Notice: JYEBAO reserves the right to make modifications deemed appropriate.