



This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.

AD-D3D3-BF	MCX Plug to MCX Plug Bulkhead 6GHz VSWR 1.2														
<table border="0"> <tr> <td data-bbox="113 342 531 394">Interface</td> <td></td> </tr> <tr> <td data-bbox="113 394 531 510">Standard</td> <td data-bbox="531 394 1482 510">IEC 61169-36</td> </tr> </table>		Interface		Standard	IEC 61169-36										
Interface															
Standard	IEC 61169-36														
<table border="0"> <tr> <td data-bbox="113 528 531 580">Electrical Data</td> <td></td> </tr> <tr> <td data-bbox="113 580 531 631">Impedance</td> <td data-bbox="531 580 1482 631">50Ω</td> </tr> <tr> <td data-bbox="113 631 531 683">Frequency Range</td> <td data-bbox="531 631 1482 683">DC to 6GHz</td> </tr> <tr> <td data-bbox="113 683 531 734">VSWR</td> <td data-bbox="531 683 1482 734">≤ 1.2 (DC To 6GHz)</td> </tr> <tr> <td data-bbox="113 734 531 786">Insulation Resistance</td> <td data-bbox="531 734 1482 786">≥ 10000MΩ</td> </tr> <tr> <td data-bbox="113 786 531 837">Dielectric Withstanding Voltage (at sea level)</td> <td data-bbox="531 786 1482 837">750 V rms</td> </tr> <tr> <td data-bbox="113 837 531 889">Working Voltage (at sea level)</td> <td data-bbox="531 837 1482 889">250 V rms</td> </tr> </table>		Electrical Data		Impedance	50Ω	Frequency Range	DC to 6GHz	VSWR	≤ 1.2 (DC To 6GHz)	Insulation Resistance	≥ 10000MΩ	Dielectric Withstanding Voltage (at sea level)	750 V rms	Working Voltage (at sea level)	250 V rms
Electrical Data															
Impedance	50Ω														
Frequency Range	DC to 6GHz														
VSWR	≤ 1.2 (DC To 6GHz)														
Insulation Resistance	≥ 10000MΩ														
Dielectric Withstanding Voltage (at sea level)	750 V rms														
Working Voltage (at sea level)	250 V rms														
<table border="0"> <tr> <td data-bbox="113 943 531 994">Mechanical Data</td> <td></td> </tr> <tr> <td data-bbox="113 994 531 1046">Engagement Force</td> <td data-bbox="531 994 1482 1046">≤ 5.6 lbs</td> </tr> <tr> <td data-bbox="113 1046 531 1097">Disengagement Force</td> <td data-bbox="531 1046 1482 1097">1.8 to 4.5 lbs</td> </tr> <tr> <td data-bbox="113 1097 531 1149">Contact Captivation-axial</td> <td data-bbox="531 1097 1482 1149">≥ 2.3 lbs</td> </tr> <tr> <td data-bbox="113 1149 531 1200">Durability (mating)</td> <td data-bbox="531 1149 1482 1200">≥ 500</td> </tr> </table>		Mechanical Data		Engagement Force	≤ 5.6 lbs	Disengagement Force	1.8 to 4.5 lbs	Contact Captivation-axial	≥ 2.3 lbs	Durability (mating)	≥ 500				
Mechanical Data															
Engagement Force	≤ 5.6 lbs														
Disengagement Force	1.8 to 4.5 lbs														
Contact Captivation-axial	≥ 2.3 lbs														
Durability (mating)	≥ 500														
<table border="0"> <tr> <td data-bbox="113 1296 531 1348">Environmental Data</td> <td></td> </tr> <tr> <td data-bbox="113 1348 531 1400">Temperature Range</td> <td data-bbox="531 1348 1482 1400">-55°C to +155°C</td> </tr> <tr> <td data-bbox="113 1400 531 1451">Thermal Shock</td> <td data-bbox="531 1400 1482 1451">MIL-STD-202, Method 107, Condition B</td> </tr> <tr> <td data-bbox="113 1451 531 1503">Moisture Resistance</td> <td data-bbox="531 1451 1482 1503">MIL-STD-202, Method 206</td> </tr> <tr> <td data-bbox="113 1503 531 1554">Corrosion</td> <td data-bbox="531 1503 1482 1554">MIL-STD-202, Method 101, Condition B</td> </tr> <tr> <td data-bbox="113 1554 531 1606">RoHS</td> <td data-bbox="531 1554 1482 1606">Compliant</td> </tr> </table>		Environmental Data		Temperature Range	-55°C to +155°C	Thermal Shock	MIL-STD-202, Method 107, Condition B	Moisture Resistance	MIL-STD-202, Method 206	Corrosion	MIL-STD-202, Method 101, Condition B	RoHS	Compliant		
Environmental Data															
Temperature Range	-55°C to +155°C														
Thermal Shock	MIL-STD-202, Method 107, Condition B														
Moisture Resistance	MIL-STD-202, Method 206														
Corrosion	MIL-STD-202, Method 101, Condition B														
RoHS	Compliant														

Notice: JYEBAO reserves the right to make modifications deemed appropriate.