

AD-M8M8	UHF Jack To UHF Jack 0.3GHz VSWR 1.2		50Ω															
<p>5/8-24UNEF-2A</p> <p>27.3 (1.075)</p> <p>5/8-24UNEF-2A</p>																		
<table border="1"> <thead> <tr> <th>Parts</th> <th>Material</th> <th>Plating (Micro-inch)</th> </tr> </thead> <tbody> <tr> <td>Ring</td> <td>Brass</td> <td>Tin-Zinc-Copper-Alloy 100 Over Copper 50</td> </tr> <tr> <td>Contact Pin</td> <td>Phosphor Bronze</td> <td>Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20</td> </tr> <tr> <td>Insulator</td> <td>Teflon</td> <td></td> </tr> <tr> <td>Coupling Nut</td> <td>Brass</td> <td>Tin-Zinc-Copper-Alloy 100 Over Copper 50</td> </tr> </tbody> </table>	Parts	Material	Plating (Micro-inch)	Ring	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50	Contact Pin	Phosphor Bronze	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20	Insulator	Teflon		Coupling Nut	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50			
Parts	Material	Plating (Micro-inch)																
Ring	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50																
Contact Pin	Phosphor Bronze	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20																
Insulator	Teflon																	
Coupling Nut	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50																
<table border="1"> <tbody> <tr> <td>Ring</td> <td>Brass</td> <td>Tin-Zinc-Copper-Alloy 100 Over Copper 50</td> </tr> <tr> <td>Contact Pin</td> <td>Phosphor Bronze</td> <td>Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20</td> </tr> <tr> <td>Insulator</td> <td>Teflon</td> <td></td> </tr> <tr> <td>Coupling Nut</td> <td>Brass</td> <td>Tin-Zinc-Copper-Alloy 100 Over Copper 50</td> </tr> </tbody> </table>				Ring	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50	Contact Pin	Phosphor Bronze	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20	Insulator	Teflon		Coupling Nut	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50			
Ring	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50																
Contact Pin	Phosphor Bronze	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20																
Insulator	Teflon																	
Coupling Nut	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50																
<p>Weight: 17.26 g</p>																		

This part number complies with RoHS.

Notice: JYBAO reserves the right to make modifications deemed appropriate.

AD-M8M8	UHF Jack To UHF Jack 0.3GHz VSWR 1.2																
<table border="0"> <tr> <td data-bbox="113 342 531 394"> <div style="border: 1px solid black; padding: 2px;">Interface</div> </td> <td data-bbox="531 342 1482 394"></td> </tr> <tr> <td data-bbox="113 394 531 539">Standard</td> <td data-bbox="531 394 1482 539">IEC 60169-12</td> </tr> </table>		<div style="border: 1px solid black; padding: 2px;">Interface</div>		Standard	IEC 60169-12												
<div style="border: 1px solid black; padding: 2px;">Interface</div>																	
Standard	IEC 60169-12																
<table border="0"> <tr> <td data-bbox="113 555 531 607"> <div style="border: 1px solid black; padding: 2px;">Electrical Data</div> </td> <td data-bbox="531 555 1482 607"></td> </tr> <tr> <td data-bbox="113 607 531 658">Impedance</td> <td data-bbox="531 607 1482 658">Non constant</td> </tr> <tr> <td data-bbox="113 658 531 710">Frequency Range</td> <td data-bbox="531 658 1482 710">DC to 300MHz</td> </tr> <tr> <td data-bbox="113 710 531 761">VSWR</td> <td data-bbox="531 710 1482 761">≤ 1.2 (DC To 300MHz)</td> </tr> <tr> <td data-bbox="113 761 531 813">Insulation Resistance</td> <td data-bbox="531 761 1482 813">≥ 5000MΩ</td> </tr> <tr> <td data-bbox="113 813 531 864">Dielectric Withstanding Voltage (at sea level)</td> <td data-bbox="531 813 1482 864">2000 V rms</td> </tr> <tr> <td data-bbox="113 864 531 916">Working Voltage (at sea level)</td> <td data-bbox="531 864 1482 916">750 V rms</td> </tr> <tr> <td data-bbox="113 916 531 967">Power Handling</td> <td data-bbox="531 916 1482 967">400W (300MHz)</td> </tr> </table>		<div style="border: 1px solid black; padding: 2px;">Electrical Data</div>		Impedance	Non constant	Frequency Range	DC to 300MHz	VSWR	≤ 1.2 (DC To 300MHz)	Insulation Resistance	≥ 5000MΩ	Dielectric Withstanding Voltage (at sea level)	2000 V rms	Working Voltage (at sea level)	750 V rms	Power Handling	400W (300MHz)
<div style="border: 1px solid black; padding: 2px;">Electrical Data</div>																	
Impedance	Non constant																
Frequency Range	DC to 300MHz																
VSWR	≤ 1.2 (DC To 300MHz)																
Insulation Resistance	≥ 5000MΩ																
Dielectric Withstanding Voltage (at sea level)	2000 V rms																
Working Voltage (at sea level)	750 V rms																
Power Handling	400W (300MHz)																
<table border="0"> <tr> <td data-bbox="113 1052 531 1104"> <div style="border: 1px solid black; padding: 2px;">Environmental Data</div> </td> <td data-bbox="531 1052 1482 1104"></td> </tr> <tr> <td data-bbox="113 1104 531 1155">Temperature Range</td> <td data-bbox="531 1104 1482 1155">-65°C to +165°C</td> </tr> <tr> <td data-bbox="113 1155 531 1207">Thermal Shock</td> <td data-bbox="531 1155 1482 1207">MIL-STD-202, Method 107, Condition B</td> </tr> <tr> <td data-bbox="113 1207 531 1258">Moisture Resistance</td> <td data-bbox="531 1207 1482 1258">MIL-STD-202, Method 206</td> </tr> <tr> <td data-bbox="113 1258 531 1310">Corrosion</td> <td data-bbox="531 1258 1482 1310">MIL-STD-202, Method 101, Condition B</td> </tr> <tr> <td data-bbox="113 1310 531 1361">RoHS</td> <td data-bbox="531 1310 1482 1361">Compliant</td> </tr> </table>		<div style="border: 1px solid black; padding: 2px;">Environmental Data</div>		Temperature Range	-65°C to +165°C	Thermal Shock	MIL-STD-202, Method 107, Condition B	Moisture Resistance	MIL-STD-202, Method 206	Corrosion	MIL-STD-202, Method 101, Condition B	RoHS	Compliant				
<div style="border: 1px solid black; padding: 2px;">Environmental Data</div>																	
Temperature Range	-65°C to +165°C																
Thermal Shock	MIL-STD-202, Method 107, Condition B																
Moisture Resistance	MIL-STD-202, Method 206																
Corrosion	MIL-STD-202, Method 101, Condition B																
RoHS	Compliant																

Notice: JYEBAO reserves the right to make modifications deemed appropriate.