

AD-MC8MC8-BF	SMC Jack to SMC Jack Bulkhead 10GHz VSWR 1.2	50Ω																		
<p style="text-align: center;">MOUNTING HOLE</p>																				
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 15%;">Parts</th> <th style="width: 15%;">Material</th> <th style="width: 70%;">Plating (Micro-inch)</th> </tr> </thead> <tbody> <tr> <td>Hex Nut</td> <td>Brass</td> <td>Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20</td> </tr> <tr> <td>Lock Washer</td> <td>Brass</td> <td>Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20</td> </tr> <tr> <td>Contact Pin</td> <td>Brass</td> <td>Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20</td> </tr> <tr> <td>Insulator</td> <td>Teflon</td> <td></td> </tr> <tr> <td>Body</td> <td>Brass</td> <td>Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20</td> </tr> </tbody> </table>			Parts	Material	Plating (Micro-inch)	Hex Nut	Brass	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20	Lock Washer	Brass	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20	Contact Pin	Brass	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20	Insulator	Teflon		Body	Brass	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20
Parts	Material	Plating (Micro-inch)																		
Hex Nut	Brass	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20																		
Lock Washer	Brass	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20																		
Contact Pin	Brass	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20																		
Insulator	Teflon																			
Body	Brass	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20																		
<p>Weight:</p>																				

This part number complies with RoHS.

Notice: JYBAO reserves the right to make modifications deemed appropriate.

AD-MC8MC8-BF	SMC Jack to SMC Jack Bulkhead 10GHz VSWR 1.2
<div style="border: 1px solid black; padding: 2px;">Interface</div> <p>Standard</p>	MIL-STD-348B
<div style="border: 1px solid black; padding: 2px;">Electrical Data</div> <p>Impedance</p> <p>Frequency Range</p> <p>VSWR</p> <p>Insertion Loss</p> <p>Insulation Resistance</p> <p>Dielectric Withstanding Voltage (at sea level)</p> <p>Working Voltage (at sea level)</p>	<p>50Ω</p> <p>DC To 10GHz</p> <p>≤ 1.2 (DC To 10GHz)</p> <p>≤ 0.1 x √f(GHz) dB</p> <p>≥ 10000MΩ</p> <p>750 V rms</p> <p>250 V rms</p>
<div style="border: 1px solid black; padding: 2px;">Mechanical Data</div> <p>Recommended Coupling Nut Torque</p> <p>Coupling Proof Torque</p> <p>Contact Captivation-axial</p> <p>Durability (mating)</p>	<p>2.2 to 3.1 in-lbs</p> <p>6.2 in-lbs</p> <p>≥ 2.25 lbs</p> <p>≥ 500</p>
<div style="border: 1px solid black; padding: 2px;">Environmental Data</div> <p>Temperature Range</p> <p>Thermal Shock</p> <p>Moisture Resistance</p> <p>Corrosion</p> <p>RoHS</p>	<p>-65°C to +165°C</p> <p>MIL-STD-202, Method 107, Condition B</p> <p>MIL-STD-202, Method 206</p> <p>MIL-STD-202, Method 101, Condition B</p> <p>Compliant</p>

Notice: JYEBAO reserves the right to make modifications deemed appropriate.