


AD-N3-4.3A/3-LP

Low PIM N Plug To 4.3-10 Screw Plug  
6GHz VSWR 1.1

50Ω



Parts	Material	Plating ( Micro-inch )
Gasket	Silicone	
Retainer Ring	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50
Ferrule	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50
Contact Pin	Brass	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20
Insulator	Teflon	
Body	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50
Coupling Nut	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50

This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.

AD-N3-4.3A/3-LP	Low PIM N Plug To 4.3-10 Screw Plug 6GHz VSWR 1.1																			
<div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">Interface</div> Standard	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 50%; text-align: center;">N</th> <th style="width: 50%; text-align: center;">4.3-10</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">MIL-STD-348B</td> <td style="text-align: center;">IEC 61169-54</td> </tr> </tbody> </table>	N	4.3-10	MIL-STD-348B	IEC 61169-54															
N	4.3-10																			
MIL-STD-348B	IEC 61169-54																			
<div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">Electrical Data</div> Impedance Frequency Range VSWR Insertion Loss Insulation Resistance Dielectric Withstanding Voltage (at sea level) Working Voltage (at sea level) Intermodulation	<table style="width: 100%; border-collapse: collapse;"> <tbody> <tr> <td style="width: 50%;"></td> <td style="width: 50%; text-align: center;">50Ω</td> </tr> <tr> <td></td> <td style="text-align: center;">DC To 6GHz</td> </tr> <tr> <td></td> <td style="text-align: center;">≤ 1.1 (DC To 6GHz)</td> </tr> <tr> <td></td> <td style="text-align: center;">≤ 0.05 x √f(GHz) dB</td> </tr> <tr> <td></td> <td style="text-align: center;">≥ 5000MΩ</td> </tr> <tr> <td></td> <td style="text-align: center;">2500 V rms</td> </tr> <tr> <td></td> <td style="text-align: center;">500 V rms</td> </tr> <tr> <td></td> <td style="text-align: center;">≤ -165dBc</td> </tr> </tbody> </table>			50Ω		DC To 6GHz		≤ 1.1 (DC To 6GHz)		≤ 0.05 x √f(GHz) dB		≥ 5000MΩ		2500 V rms		500 V rms		≤ -165dBc		
	50Ω																			
	DC To 6GHz																			
	≤ 1.1 (DC To 6GHz)																			
	≤ 0.05 x √f(GHz) dB																			
	≥ 5000MΩ																			
	2500 V rms																			
	500 V rms																			
	≤ -165dBc																			
<div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">Mechanical Data</div> Recommended Coupling Nut Torque Coupling Proof Torque Coupling Nut Retention Force Contact Captivation-axial Durability (mating)	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 50%;"></th> <th style="width: 25%; text-align: center;">N</th> <th style="width: 25%; text-align: center;">4.3-10</th> </tr> </thead> <tbody> <tr> <td></td> <td style="text-align: center;">6 to 10 in-lbs</td> <td style="text-align: center;">44 in-lbs (screw type)</td> </tr> <tr> <td></td> <td style="text-align: center;">15 in-lbs</td> <td style="text-align: center;">70 in-lbs (screw type)</td> </tr> <tr> <td></td> <td style="text-align: center;">≥ 101.2 lbs</td> <td style="text-align: center;">≥ 101.2 lbs</td> </tr> <tr> <td></td> <td style="text-align: center;">≥ 6.3 lbs</td> <td style="text-align: center;">≥ 6.3 lbs</td> </tr> <tr> <td></td> <td style="text-align: center;">≥ 500</td> <td style="text-align: center;">≥ 100</td> </tr> </tbody> </table>			N	4.3-10		6 to 10 in-lbs	44 in-lbs (screw type)		15 in-lbs	70 in-lbs (screw type)		≥ 101.2 lbs	≥ 101.2 lbs		≥ 6.3 lbs	≥ 6.3 lbs		≥ 500	≥ 100
	N	4.3-10																		
	6 to 10 in-lbs	44 in-lbs (screw type)																		
	15 in-lbs	70 in-lbs (screw type)																		
	≥ 101.2 lbs	≥ 101.2 lbs																		
	≥ 6.3 lbs	≥ 6.3 lbs																		
	≥ 500	≥ 100																		
<div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">Environmental Data</div> Temperature Range Thermal Shock Moisture Resistance Corrosion RoHS	<table style="width: 100%; border-collapse: collapse;"> <tbody> <tr> <td style="width: 50%;"></td> <td style="width: 50%; text-align: center;">-65°C to +165°C</td> </tr> <tr> <td></td> <td style="text-align: center;">MIL-STD-202, Method 107, Condition B</td> </tr> <tr> <td></td> <td style="text-align: center;">MIL-STD-202, Method 206</td> </tr> <tr> <td></td> <td style="text-align: center;">MIL-STD-202, Method 101, Condition B</td> </tr> <tr> <td></td> <td style="text-align: center;">Compliant</td> </tr> </tbody> </table>			-65°C to +165°C		MIL-STD-202, Method 107, Condition B		MIL-STD-202, Method 206		MIL-STD-202, Method 101, Condition B		Compliant								
	-65°C to +165°C																			
	MIL-STD-202, Method 107, Condition B																			
	MIL-STD-202, Method 206																			
	MIL-STD-202, Method 101, Condition B																			
	Compliant																			