

AD-N3M3		N Plug To UHF Plug 0.3GHz VSWR 1.2	
Parts	Material	Plating (Micro-inch)	
Gasket	Silicone		
Insulator	Teflon		
Retainer Ring	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50	
Contact Pin(N)	Brass	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20	
Contact Pin(UHF)	Brass	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20	
Body	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50	
Coupling Nut	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50	
Weight: 50.46 g			

This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.

AD-N3M3	N Plug To UHF Plug 0.3GHz VSWR 1.2	
<div style="border: 1px solid black; padding: 2px;">Interface</div> <p>Standard</p>	N	UHF
	MIL-STD-348B	IEC 60169-12
<div style="border: 1px solid black; padding: 2px;">Electrical Data</div> <p>Impedance</p> <p>Frequency Range</p> <p>VSWR</p> <p>Insertion Loss</p> <p>Insulation Resistance</p> <p>Dielectric Withstanding Voltage (at sea level)</p> <p>Working Voltage (at sea level)</p>	<p>Non Constant</p> <p>DC To 300MHz</p> <p>≤ 1.2 (DC To 300MHz)</p> <p>$\leq 0.05 \times \sqrt{f}$(GHz) dB</p> <p>$\geq 5000\Omega$</p> <p>2000 V rms</p> <p>750 V rms</p>	
<div style="border: 1px solid black; padding: 2px;">Mechanical Data</div> <p>Recommended Coupling Nut Torque</p> <p>Coupling Proof Torque</p> <p>Coupling Nut Retention Force</p> <p>Contact Captivation-axial</p> <p>Durability (mating)</p>	N	UHF
	6 to 10 in-lbs	NA
	15 in-lbs	NA
	≥ 101.2 lbs	NA
	≥ 6.3 lbs	NA
	≥ 500	NA
<div style="border: 1px solid black; padding: 2px;">Environmental Data</div> <p>Temperature Range</p> <p>Thermal Shock</p> <p>Moisture Resistance</p> <p>Corrosion</p> <p>RoHS</p>	<p>-65°C to +165°C</p> <p>MIL-STD-202, Method 107, Condition B</p> <p>MIL-STD-202, Method 206</p> <p>MIL-STD-202, Method 101, Condition B</p> <p>Compliant</p>	

Notice: JYEBAO reserves the right to make modifications deemed appropriate.