

AD-N3N8	N Plug To N Jack 11GHz VSWR 1.2		50Ω
Parts	Material	Plating (Micro-inch)	
Coupling Nut	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50	
Retainer Ring	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50	
Gasket	Silicone		
Contact Body	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50	
Contact Pin	Beryllium Copper	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20	
Insulator	Teflon		
Body	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50	
Weight: 52.62 g			

This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.

AD-N3N8	<b>N Plug To N Jack 11GHz VSWR 1.2</b>																
<table border="0" style="width: 100%;"> <tr> <td data-bbox="129 342 531 394" style="border: 1px solid black;"><b>Interface</b></td> <td></td> </tr> <tr> <td data-bbox="129 394 791 586">Standard</td> <td data-bbox="791 394 1482 586" style="text-align: center;">MIL-STD-348B</td> </tr> </table>		<b>Interface</b>		Standard	MIL-STD-348B												
<b>Interface</b>																	
Standard	MIL-STD-348B																
<table border="0" style="width: 100%;"> <tr> <td data-bbox="129 604 531 656" style="border: 1px solid black;"><b>Electrical Data</b></td> <td></td> </tr> <tr> <td data-bbox="129 656 791 701">Impedance</td> <td data-bbox="791 656 1482 701" style="text-align: center;">50Ω</td> </tr> <tr> <td data-bbox="129 701 791 745">Frequency Range</td> <td data-bbox="791 701 1482 745" style="text-align: center;">DC to 11GHz</td> </tr> <tr> <td data-bbox="129 745 791 790">VSWR</td> <td data-bbox="791 745 1482 790" style="text-align: center;">≤ 1.2 (DC To 11GHz)</td> </tr> <tr> <td data-bbox="129 790 791 835">Insertion Loss</td> <td data-bbox="791 790 1482 835" style="text-align: center;">≤ 0.05 x √f(GHz) dB</td> </tr> <tr> <td data-bbox="129 835 791 880">Insulation Resistance</td> <td data-bbox="791 835 1482 880" style="text-align: center;">≥ 5000MΩ</td> </tr> <tr> <td data-bbox="129 880 791 925">Dielectric Withstanding Voltage (at sea level)</td> <td data-bbox="791 880 1482 925" style="text-align: center;">2500 V rms</td> </tr> <tr> <td data-bbox="129 925 791 969">Working Voltage (at sea level)</td> <td data-bbox="791 925 1482 969" style="text-align: center;">1000 V rms</td> </tr> </table>		<b>Electrical Data</b>		Impedance	50Ω	Frequency Range	DC to 11GHz	VSWR	≤ 1.2 (DC To 11GHz)	Insertion Loss	≤ 0.05 x √f(GHz) dB	Insulation Resistance	≥ 5000MΩ	Dielectric Withstanding Voltage (at sea level)	2500 V rms	Working Voltage (at sea level)	1000 V rms
<b>Electrical Data</b>																	
Impedance	50Ω																
Frequency Range	DC to 11GHz																
VSWR	≤ 1.2 (DC To 11GHz)																
Insertion Loss	≤ 0.05 x √f(GHz) dB																
Insulation Resistance	≥ 5000MΩ																
Dielectric Withstanding Voltage (at sea level)	2500 V rms																
Working Voltage (at sea level)	1000 V rms																
<table border="0" style="width: 100%;"> <tr> <td data-bbox="129 1102 531 1153" style="border: 1px solid black;"><b>Mechanical Data</b></td> <td></td> </tr> <tr> <td data-bbox="129 1153 791 1198">Recommended Coupling Nut Torque</td> <td data-bbox="791 1153 1482 1198" style="text-align: center;">6 to 10 in-lbs</td> </tr> <tr> <td data-bbox="129 1198 791 1243">Coupling Proof Torque</td> <td data-bbox="791 1198 1482 1243" style="text-align: center;">15 in-lbs</td> </tr> <tr> <td data-bbox="129 1243 791 1288">Coupling Nut Retention Force</td> <td data-bbox="791 1243 1482 1288" style="text-align: center;">≥ 101.2 lbs</td> </tr> <tr> <td data-bbox="129 1288 791 1332">Contact Captivation-axial</td> <td data-bbox="791 1288 1482 1332" style="text-align: center;">≥ 6.3 lbs</td> </tr> <tr> <td data-bbox="129 1332 791 1377">Durability (mating)</td> <td data-bbox="791 1332 1482 1377" style="text-align: center;">≥ 500</td> </tr> </table>		<b>Mechanical Data</b>		Recommended Coupling Nut Torque	6 to 10 in-lbs	Coupling Proof Torque	15 in-lbs	Coupling Nut Retention Force	≥ 101.2 lbs	Contact Captivation-axial	≥ 6.3 lbs	Durability (mating)	≥ 500				
<b>Mechanical Data</b>																	
Recommended Coupling Nut Torque	6 to 10 in-lbs																
Coupling Proof Torque	15 in-lbs																
Coupling Nut Retention Force	≥ 101.2 lbs																
Contact Captivation-axial	≥ 6.3 lbs																
Durability (mating)	≥ 500																
<table border="0" style="width: 100%;"> <tr> <td data-bbox="129 1503 531 1554" style="border: 1px solid black;"><b>Environmental Data</b></td> <td></td> </tr> <tr> <td data-bbox="129 1554 791 1599">Temperature Range</td> <td data-bbox="791 1554 1482 1599" style="text-align: center;">-65°C to +165°C</td> </tr> <tr> <td data-bbox="129 1599 791 1644">Thermal Shock</td> <td data-bbox="791 1599 1482 1644" style="text-align: center;">MIL-STD-202, Method 107, Condition B</td> </tr> <tr> <td data-bbox="129 1644 791 1688">Moisture Resistance</td> <td data-bbox="791 1644 1482 1688" style="text-align: center;">MIL-STD-202, Method 206</td> </tr> <tr> <td data-bbox="129 1688 791 1733">Corrosion</td> <td data-bbox="791 1688 1482 1733" style="text-align: center;">MIL-STD-202, Method 101, Condition B</td> </tr> <tr> <td data-bbox="129 1733 791 1778">RoHS</td> <td data-bbox="791 1733 1482 1778" style="text-align: center;">Compliant</td> </tr> </table>		<b>Environmental Data</b>		Temperature Range	-65°C to +165°C	Thermal Shock	MIL-STD-202, Method 107, Condition B	Moisture Resistance	MIL-STD-202, Method 206	Corrosion	MIL-STD-202, Method 101, Condition B	RoHS	Compliant				
<b>Environmental Data</b>																	
Temperature Range	-65°C to +165°C																
Thermal Shock	MIL-STD-202, Method 107, Condition B																
Moisture Resistance	MIL-STD-202, Method 206																
Corrosion	MIL-STD-202, Method 101, Condition B																
RoHS	Compliant																

Notice: JYEBAO reserves the right to make modifications deemed appropriate.

# AD-N3N8



