

AD-N8LC3	N Jack To LC Plug 1GHz VSWR 1.2	<b>50Ω</b>																					
NOTE: Small LC Standard Plug.																							
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 25%;">Parts</th> <th style="width: 25%;">Material</th> <th style="width: 50%;">Plating (Micro-inch)</th> </tr> </thead> <tbody> <tr> <td>Renber Ring</td> <td>Brass</td> <td>Tin-Zinc-Copper-Alloy 100 Over Copper 50</td> </tr> <tr> <td>Gasket</td> <td>Silicon</td> <td></td> </tr> <tr> <td>Contact Pin</td> <td>Beryllium Copper</td> <td>Silver 150 Over Copper 50</td> </tr> <tr> <td>Insulator</td> <td>Teflon</td> <td></td> </tr> <tr> <td>Body</td> <td>Brass</td> <td>Tin-Zinc-Copper-Alloy 100 Over Copper 50</td> </tr> <tr> <td>Coupling Nut</td> <td>Brass</td> <td>Tin-Zinc-Copper-Alloy 100 Over Copper 50</td> </tr> </tbody> </table>			Parts	Material	Plating (Micro-inch)	Renber Ring	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50	Gasket	Silicon		Contact Pin	Beryllium Copper	Silver 150 Over Copper 50	Insulator	Teflon		Body	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50	Coupling Nut	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50
Parts	Material	Plating (Micro-inch)																					
Renber Ring	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50																					
Gasket	Silicon																						
Contact Pin	Beryllium Copper	Silver 150 Over Copper 50																					
Insulator	Teflon																						
Body	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50																					
Coupling Nut	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50																					
Weight:																							

This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.

AD-N8LC3	N Jack To LC Plug 1GHz VSWR 1.2											
<div style="border: 1px solid black; padding: 2px;">Interface</div> <p>Standard</p>	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 50%;">N</th> <th style="width: 50%;">LC</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">MIL-STD-348B</td> <td style="text-align: center;">MIL-STD-348B</td> </tr> </tbody> </table>	N	LC	MIL-STD-348B	MIL-STD-348B							
N	LC											
MIL-STD-348B	MIL-STD-348B											
<div style="border: 1px solid black; padding: 2px;">Electrical Data</div> <p>Impedance</p> <p>Frequency Range</p> <p>VSWR</p> <p>Insertion Loss</p> <p>Insulation Resistance</p> <p>Dielectric Withstanding Voltage (at sea level)</p> <p>Working Voltage (at sea level)</p>	<p style="text-align: center;">50Ω</p> <p style="text-align: center;">DC To 1GHz</p> <p style="text-align: center;">≤ 1.2 (DC To 1GHz)</p> <p style="text-align: center;">≤ 0.04 x √f(GHz) dB</p> <p style="text-align: center;">≥ 5000MΩ</p> <p style="text-align: center;">2500 V rms</p> <p style="text-align: center;">1000 V rms</p>											
<div style="border: 1px solid black; padding: 2px;">Mechanical Data</div> <p>Recommended Coupling Nut Torque</p> <p>Coupling Proof Torque</p> <p>Contact Captivation-axial</p> <p>Durability (mating)</p>	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 50%;">N</th> <th style="width: 50%;">LC</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">6 to 10 in-lbs</td> <td style="text-align: center;">NA</td> </tr> <tr> <td style="text-align: center;">15 in-lbs</td> <td style="text-align: center;">NA</td> </tr> <tr> <td style="text-align: center;">≥ 6.3 lbs</td> <td style="text-align: center;">NA</td> </tr> <tr> <td style="text-align: center;">≥ 500</td> <td style="text-align: center;">≥ 500</td> </tr> </tbody> </table>		N	LC	6 to 10 in-lbs	NA	15 in-lbs	NA	≥ 6.3 lbs	NA	≥ 500	≥ 500
N	LC											
6 to 10 in-lbs	NA											
15 in-lbs	NA											
≥ 6.3 lbs	NA											
≥ 500	≥ 500											
<div style="border: 1px solid black; padding: 2px;">Environmental Data</div> <p>Temperature Range</p> <p>Thermal Shock</p> <p>Moisture Resistance</p> <p>Corrosion</p> <p>RoHS</p>	<p style="text-align: center;">-65°C to +165°C</p> <p style="text-align: center;">MIL-STD-202, Method 107, Condition B</p> <p style="text-align: center;">MIL-STD-202, Method 206</p> <p style="text-align: center;">MIL-STD-202, Method 101, Condition B</p> <p style="text-align: center;">Compliant</p>											

Notice: JYEBAO reserves the right to make modifications deemed appropriate.