

AD-N8N8-P4-18	N Jack To N Jack With 4-Hole Flange 18GHz VSWR 1.2	50Ω
<p style="text-align: center;">MOUNTING HOLE:</p>		
Parts	Material	Plating (Micro-inch)
Contact Pin	Beryllium Copper	Gold 4 Over Nickel Phosphorous Alloy 80 Over Copper 20
Body	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50
Insulator	PTFE	
Weight:		

This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.

AD-N8N8-P4-18	N Jack To N Jack With 4-Hole Flange 18GHz VSWR 1.2																
<table border="0" style="width: 100%;"> <tr> <td colspan="2" data-bbox="129 342 531 394">Interface</td> </tr> <tr> <td data-bbox="129 394 794 533">Standard</td> <td data-bbox="794 394 1482 533" style="text-align: center;">MIL-STD-348B</td> </tr> </table>		Interface		Standard	MIL-STD-348B												
Interface																	
Standard	MIL-STD-348B																
<table border="0" style="width: 100%;"> <tr> <td colspan="2" data-bbox="129 560 531 611">Electrical Data</td> </tr> <tr> <td data-bbox="129 611 794 656">Impedance</td> <td data-bbox="794 611 1482 656" style="text-align: center;">50Ω</td> </tr> <tr> <td data-bbox="129 656 794 701">Frequency Range</td> <td data-bbox="794 656 1482 701" style="text-align: center;">DC to 18GHz</td> </tr> <tr> <td data-bbox="129 701 794 745">VSWR</td> <td data-bbox="794 701 1482 745" style="text-align: center;">≤ 1.2 (DC To 18GHz)</td> </tr> <tr> <td data-bbox="129 745 794 790">Insertion Loss</td> <td data-bbox="794 745 1482 790" style="text-align: center;">≤ 0.05 x √f(GHz) dB</td> </tr> <tr> <td data-bbox="129 790 794 835">Insulation Resistance</td> <td data-bbox="794 790 1482 835" style="text-align: center;">≥ 5000MΩ</td> </tr> <tr> <td data-bbox="129 835 794 880">Dielectric Withstanding Voltage (at sea level)</td> <td data-bbox="794 835 1482 880" style="text-align: center;">2500 V rms</td> </tr> <tr> <td data-bbox="129 880 794 925">Working Voltage (at sea level)</td> <td data-bbox="794 880 1482 925" style="text-align: center;">1000 V rms</td> </tr> </table>		Electrical Data		Impedance	50Ω	Frequency Range	DC to 18GHz	VSWR	≤ 1.2 (DC To 18GHz)	Insertion Loss	≤ 0.05 x √f(GHz) dB	Insulation Resistance	≥ 5000MΩ	Dielectric Withstanding Voltage (at sea level)	2500 V rms	Working Voltage (at sea level)	1000 V rms
Electrical Data																	
Impedance	50Ω																
Frequency Range	DC to 18GHz																
VSWR	≤ 1.2 (DC To 18GHz)																
Insertion Loss	≤ 0.05 x √f(GHz) dB																
Insulation Resistance	≥ 5000MΩ																
Dielectric Withstanding Voltage (at sea level)	2500 V rms																
Working Voltage (at sea level)	1000 V rms																
<table border="0" style="width: 100%;"> <tr> <td colspan="2" data-bbox="129 1057 531 1108">Mechanical Data</td> </tr> <tr> <td data-bbox="129 1108 794 1153">Recommended Coupling Nut Torque</td> <td data-bbox="794 1108 1482 1153" style="text-align: center;">6 to 10 in-lbs</td> </tr> <tr> <td data-bbox="129 1153 794 1198">Coupling Proof Torque</td> <td data-bbox="794 1153 1482 1198" style="text-align: center;">15 in-lbs</td> </tr> <tr> <td data-bbox="129 1198 794 1243">Contact Captivation-axial</td> <td data-bbox="794 1198 1482 1243" style="text-align: center;">≥ 6.3 lbs</td> </tr> <tr> <td data-bbox="129 1243 794 1288">Durability (mating)</td> <td data-bbox="794 1243 1482 1288" style="text-align: center;">≥ 500</td> </tr> </table>		Mechanical Data		Recommended Coupling Nut Torque	6 to 10 in-lbs	Coupling Proof Torque	15 in-lbs	Contact Captivation-axial	≥ 6.3 lbs	Durability (mating)	≥ 500						
Mechanical Data																	
Recommended Coupling Nut Torque	6 to 10 in-lbs																
Coupling Proof Torque	15 in-lbs																
Contact Captivation-axial	≥ 6.3 lbs																
Durability (mating)	≥ 500																
<table border="0" style="width: 100%;"> <tr> <td colspan="2" data-bbox="129 1456 531 1507">Environmental Data</td> </tr> <tr> <td data-bbox="129 1507 794 1552">Temperature Range</td> <td data-bbox="794 1507 1482 1552" style="text-align: center;">-65°C to +165°C</td> </tr> <tr> <td data-bbox="129 1552 794 1597">Thermal Shock</td> <td data-bbox="794 1552 1482 1597" style="text-align: center;">MIL-STD-202, Method 107, Condition B</td> </tr> <tr> <td data-bbox="129 1597 794 1641">Moisture Resistance</td> <td data-bbox="794 1597 1482 1641" style="text-align: center;">MIL-STD-202, Method 206</td> </tr> <tr> <td data-bbox="129 1641 794 1686">Corrosion</td> <td data-bbox="794 1641 1482 1686" style="text-align: center;">MIL-STD-202, Method 101, Condition B</td> </tr> <tr> <td data-bbox="129 1686 794 1731">RoHS</td> <td data-bbox="794 1686 1482 1731" style="text-align: center;">Compliant</td> </tr> </table>		Environmental Data		Temperature Range	-65°C to +165°C	Thermal Shock	MIL-STD-202, Method 107, Condition B	Moisture Resistance	MIL-STD-202, Method 206	Corrosion	MIL-STD-202, Method 101, Condition B	RoHS	Compliant				
Environmental Data																	
Temperature Range	-65°C to +165°C																
Thermal Shock	MIL-STD-202, Method 107, Condition B																
Moisture Resistance	MIL-STD-202, Method 206																
Corrosion	MIL-STD-202, Method 101, Condition B																
RoHS	Compliant																

Notice: JYEBAO reserves the right to make modifications deemed appropriate.

