


ADS-K3K3-1.1

2.92mm Plug To 2.92mm Plug  
40GHz VSWR 1.1

50Ω



Parts	Material	Plating ( Micro-inch )
Retainer Ring	Beryllium Copper	Tin-Zinc-Copper-Alloy 100 Over Copper 50
Gasket	Silicone	
Contact Pin	Beryllium Copper	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20
Insulator	PPO	
Body	Stainless Steel	Passivated
Coupling Nut	Stainless Steel	Passivated

This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.

ADS-K3K3-1.1	2.92mm Plug To 2.92mm Plug 40GHz VSWR 1.1																		
<table border="0"> <tr> <td colspan="2" data-bbox="129 342 531 394"><b>Interface</b></td> </tr> <tr> <td data-bbox="129 400 794 434">Standard</td> <td data-bbox="794 400 1482 434">MIL-STD-348B</td> </tr> <tr> <td data-bbox="129 445 794 479">Mechanically compatible with</td> <td data-bbox="794 445 1482 479">3.5 &amp; SMA</td> </tr> </table>		<b>Interface</b>		Standard	MIL-STD-348B	Mechanically compatible with	3.5 & SMA												
<b>Interface</b>																			
Standard	MIL-STD-348B																		
Mechanically compatible with	3.5 & SMA																		
<table border="0"> <tr> <td colspan="2" data-bbox="129 602 531 654"><b>Electrical Data</b></td> </tr> <tr> <td data-bbox="129 660 794 694">Impedance</td> <td data-bbox="794 660 1482 694">50Ω</td> </tr> <tr> <td data-bbox="129 705 794 739">Frequency Range</td> <td data-bbox="794 705 1482 739">DC to 40GHz</td> </tr> <tr> <td data-bbox="129 750 794 784">VSWR</td> <td data-bbox="794 750 1482 784">≤ 1.1 (DC To 40GHz)</td> </tr> <tr> <td data-bbox="129 795 794 828">Insertion Loss</td> <td data-bbox="794 795 1482 828">≤ 0.04 x √f(GHz) dB</td> </tr> <tr> <td data-bbox="129 840 794 873">Insulation Resistance</td> <td data-bbox="794 840 1482 873">≥ 5000MΩ</td> </tr> <tr> <td data-bbox="129 884 794 918">Dielectric Withstanding Voltage (at sea level)</td> <td data-bbox="794 884 1482 918">750 V rms</td> </tr> <tr> <td data-bbox="129 929 794 963">Working Voltage (at sea level)</td> <td data-bbox="794 929 1482 963">250 V rms</td> </tr> <tr> <td data-bbox="129 974 794 1008">RF Leakage</td> <td data-bbox="794 974 1482 1008">≥ 100dB to 1GHz</td> </tr> </table>		<b>Electrical Data</b>		Impedance	50Ω	Frequency Range	DC to 40GHz	VSWR	≤ 1.1 (DC To 40GHz)	Insertion Loss	≤ 0.04 x √f(GHz) dB	Insulation Resistance	≥ 5000MΩ	Dielectric Withstanding Voltage (at sea level)	750 V rms	Working Voltage (at sea level)	250 V rms	RF Leakage	≥ 100dB to 1GHz
<b>Electrical Data</b>																			
Impedance	50Ω																		
Frequency Range	DC to 40GHz																		
VSWR	≤ 1.1 (DC To 40GHz)																		
Insertion Loss	≤ 0.04 x √f(GHz) dB																		
Insulation Resistance	≥ 5000MΩ																		
Dielectric Withstanding Voltage (at sea level)	750 V rms																		
Working Voltage (at sea level)	250 V rms																		
RF Leakage	≥ 100dB to 1GHz																		
<table border="0"> <tr> <td colspan="2" data-bbox="129 1151 531 1202"><b>Mechanical Data</b></td> </tr> <tr> <td data-bbox="129 1209 794 1243">Recommended Coupling Nut Torque</td> <td data-bbox="794 1209 1482 1243">11.47 in-lbs</td> </tr> <tr> <td data-bbox="129 1254 794 1288">Coupling Proof Torque</td> <td data-bbox="794 1254 1482 1288">15 in-lbs</td> </tr> <tr> <td data-bbox="129 1299 794 1332">Contact Captivation-axial</td> <td data-bbox="794 1299 1482 1332">≥ 4.9 lbs</td> </tr> <tr> <td data-bbox="129 1344 794 1377">Durability (mating)</td> <td data-bbox="794 1344 1482 1377">≥ 500</td> </tr> </table>		<b>Mechanical Data</b>		Recommended Coupling Nut Torque	11.47 in-lbs	Coupling Proof Torque	15 in-lbs	Contact Captivation-axial	≥ 4.9 lbs	Durability (mating)	≥ 500								
<b>Mechanical Data</b>																			
Recommended Coupling Nut Torque	11.47 in-lbs																		
Coupling Proof Torque	15 in-lbs																		
Contact Captivation-axial	≥ 4.9 lbs																		
Durability (mating)	≥ 500																		
<table border="0"> <tr> <td colspan="2" data-bbox="129 1505 531 1556"><b>Environmental Data</b></td> </tr> <tr> <td data-bbox="129 1563 794 1597">Temperature Range</td> <td data-bbox="794 1563 1482 1597">-55°C to +105°C</td> </tr> <tr> <td data-bbox="129 1608 794 1641">Thermal Shock</td> <td data-bbox="794 1608 1482 1641">MIL-STD-202, Method 107, Condition B</td> </tr> <tr> <td data-bbox="129 1653 794 1686">Moisture Resistance</td> <td data-bbox="794 1653 1482 1686">MIL-STD-202, Method 206</td> </tr> <tr> <td data-bbox="129 1697 794 1731">Corrosion</td> <td data-bbox="794 1697 1482 1731">MIL-STD-202, Method 101, Condition B</td> </tr> <tr> <td data-bbox="129 1742 794 1776">RoHS</td> <td data-bbox="794 1742 1482 1776">Compliant</td> </tr> </table>		<b>Environmental Data</b>		Temperature Range	-55°C to +105°C	Thermal Shock	MIL-STD-202, Method 107, Condition B	Moisture Resistance	MIL-STD-202, Method 206	Corrosion	MIL-STD-202, Method 101, Condition B	RoHS	Compliant						
<b>Environmental Data</b>																			
Temperature Range	-55°C to +105°C																		
Thermal Shock	MIL-STD-202, Method 107, Condition B																		
Moisture Resistance	MIL-STD-202, Method 206																		
Corrosion	MIL-STD-202, Method 101, Condition B																		
RoHS	Compliant																		

Notice: JYEBAO reserves the right to make modifications deemed appropriate.

# ADS-K3K3-1.1

