


ADS-K8SA3-1.25

2.92mm Jack to SSMA Plug
40GHz VSWR 1.25

50Ω



Parts	Material	Plating (Micro-inch)
Coupling Nut	Stainless Steel	Passivated
Body	Stainless Steel	Passivated
Insulator (2.92)	PEI	
Contact Pin	Beryllium Copper	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20
Gasket	Silicone	
Retainer Ring	Beryllium Copper	Tin-Zinc-Copper-Alloy 100 Over Copper 50
Insulator (SSMA)	PTFE	

This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.

ADS-K8SA3-1.25	2.92mm Jack to SSMA Plug 40GHz VSWR 1.25													
<div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">Interface</div> Standard Mechanically compatible with	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 50%;">2.92</th> <th style="width: 50%;">SSMA</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">MIL-STD-348B</td> <td style="text-align: center;">MIL-STD-348B</td> </tr> <tr> <td style="text-align: center;">3.5 & SMA</td> <td></td> </tr> </tbody> </table>	2.92	SSMA	MIL-STD-348B	MIL-STD-348B	3.5 & SMA								
2.92	SSMA													
MIL-STD-348B	MIL-STD-348B													
3.5 & SMA														
<div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">Electrical Data</div> Impedance Frequency Range VSWR Insertion Loss Insulation Resistance Dielectric Withstanding Voltage (at sea level) Working Voltage (at sea level)	<table style="width: 100%;"> <tr> <td style="width: 50%;">50Ω</td> <td style="width: 50%;">DC To 40GHz</td> </tr> <tr> <td>≤ 1.25 (DC To 40GHz)</td> <td></td> </tr> <tr> <td>≤ 0.05 x √f(GHz) dB</td> <td></td> </tr> <tr> <td>≥ 5000MΩ</td> <td></td> </tr> <tr> <td>750 V rms</td> <td></td> </tr> <tr> <td>250 V rms</td> <td></td> </tr> </table>		50Ω	DC To 40GHz	≤ 1.25 (DC To 40GHz)		≤ 0.05 x √f(GHz) dB		≥ 5000MΩ		750 V rms		250 V rms	
50Ω	DC To 40GHz													
≤ 1.25 (DC To 40GHz)														
≤ 0.05 x √f(GHz) dB														
≥ 5000MΩ														
750 V rms														
250 V rms														
<div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">Mechanical Data</div> Recommended Coupling Nut Torque Coupling Proof Torque Contact Captivation-axial Durability (mating)	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 50%;">2.92</th> <th style="width: 50%;">SSMA</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">11.47 in-lbs</td> <td style="text-align: center;">4 in-lbs</td> </tr> <tr> <td style="text-align: center;">15 in-lbs</td> <td style="text-align: center;">5 in-lbs</td> </tr> <tr> <td style="text-align: center;">≥ 4.9 lbs</td> <td style="text-align: center;">≥ 5 lbs</td> </tr> <tr> <td style="text-align: center;">≥ 500</td> <td style="text-align: center;">≥ 500</td> </tr> </tbody> </table>		2.92	SSMA	11.47 in-lbs	4 in-lbs	15 in-lbs	5 in-lbs	≥ 4.9 lbs	≥ 5 lbs	≥ 500	≥ 500		
2.92	SSMA													
11.47 in-lbs	4 in-lbs													
15 in-lbs	5 in-lbs													
≥ 4.9 lbs	≥ 5 lbs													
≥ 500	≥ 500													
<div style="border: 1px solid black; padding: 2px; margin-bottom: 5px;">Environmental Data</div> Temperature Range Thermal Shock Moisture Resistance Corrosion RoHS	<table style="width: 100%;"> <tr> <td style="width: 50%;">-40°C to +165°C</td> <td style="width: 50%;">MIL-STD-202, Method 107, Condition B</td> </tr> <tr> <td></td> <td>MIL-STD-202, Method 206</td> </tr> <tr> <td></td> <td>MIL-STD-202, Method 101, Condition B</td> </tr> <tr> <td></td> <td>Compliant</td> </tr> </table>		-40°C to +165°C	MIL-STD-202, Method 107, Condition B		MIL-STD-202, Method 206		MIL-STD-202, Method 101, Condition B		Compliant				
-40°C to +165°C	MIL-STD-202, Method 107, Condition B													
	MIL-STD-202, Method 206													
	MIL-STD-202, Method 101, Condition B													
	Compliant													