


ADS-PC8PC8-1.15

3.5mm Jack To 3.5mm Jack
34.5GHz VSWR 1.15

50Ω



Parts	Material	Plating (Micro-inch)
Contact Pin	Beryllium Copper	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20
Insulator	PPO	
Body	Stainless Steel	Passivated


This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.


ADS-PC8PC8-1.15	3.5mm Jack To 3.5mm Jack 34.5GHz VSWR 1.15																		
<table border="0"> <tr> <td colspan="2" data-bbox="129 342 531 394">Interface</td> </tr> <tr> <td data-bbox="129 400 794 434">Standard</td> <td data-bbox="794 400 1482 434">IEC60169-23</td> </tr> <tr> <td data-bbox="129 450 794 483">Mechanically compatible with</td> <td data-bbox="794 450 1482 483">2.92 & SMA</td> </tr> </table>		Interface		Standard	IEC60169-23	Mechanically compatible with	2.92 & SMA												
Interface																			
Standard	IEC60169-23																		
Mechanically compatible with	2.92 & SMA																		
<table border="0"> <tr> <td colspan="2" data-bbox="129 602 531 654">Electrical Data</td> </tr> <tr> <td data-bbox="129 660 794 694">Impedance</td> <td data-bbox="794 660 1482 694">50Ω</td> </tr> <tr> <td data-bbox="129 710 794 743">Frequency Range</td> <td data-bbox="794 710 1482 743">DC to 34.5GHz</td> </tr> <tr> <td data-bbox="129 759 794 792">VSWR</td> <td data-bbox="794 759 1482 792">≤ 1.15 (DC To 34.5GHz)</td> </tr> <tr> <td data-bbox="129 808 794 842">Insertion Loss</td> <td data-bbox="794 808 1482 842">≤ 0.05 x √f(GHz) dB</td> </tr> <tr> <td data-bbox="129 857 794 891">Insulation Resistance</td> <td data-bbox="794 857 1482 891">≥ 5000MΩ</td> </tr> <tr> <td data-bbox="129 907 794 940">Dielectric Withstanding Voltage (at sea level)</td> <td data-bbox="794 907 1482 940">1000 V rms</td> </tr> <tr> <td data-bbox="129 956 794 990">Working Voltage (at sea level)</td> <td data-bbox="794 956 1482 990">335 V rms</td> </tr> <tr> <td data-bbox="129 1005 794 1039">RF Leakage</td> <td data-bbox="794 1005 1482 1039">≥ 100dB to 1GHz</td> </tr> </table>		Electrical Data		Impedance	50Ω	Frequency Range	DC to 34.5GHz	VSWR	≤ 1.15 (DC To 34.5GHz)	Insertion Loss	≤ 0.05 x √f(GHz) dB	Insulation Resistance	≥ 5000MΩ	Dielectric Withstanding Voltage (at sea level)	1000 V rms	Working Voltage (at sea level)	335 V rms	RF Leakage	≥ 100dB to 1GHz
Electrical Data																			
Impedance	50Ω																		
Frequency Range	DC to 34.5GHz																		
VSWR	≤ 1.15 (DC To 34.5GHz)																		
Insertion Loss	≤ 0.05 x √f(GHz) dB																		
Insulation Resistance	≥ 5000MΩ																		
Dielectric Withstanding Voltage (at sea level)	1000 V rms																		
Working Voltage (at sea level)	335 V rms																		
RF Leakage	≥ 100dB to 1GHz																		
<table border="0"> <tr> <td colspan="2" data-bbox="129 1151 531 1202">Mechanical Data</td> </tr> <tr> <td data-bbox="129 1209 794 1243">Recommended Coupling Nut Torque</td> <td data-bbox="794 1209 1482 1243">7.1 to 9.7 in-lbs</td> </tr> <tr> <td data-bbox="129 1258 794 1292">Coupling Proof Torque</td> <td data-bbox="794 1258 1482 1292">15 in-lbs</td> </tr> <tr> <td data-bbox="129 1308 794 1341">Contact Captivation-axial</td> <td data-bbox="794 1308 1482 1341">≥ 6.1 lbs</td> </tr> <tr> <td data-bbox="129 1357 794 1391">Durability (mating)</td> <td data-bbox="794 1357 1482 1391">≥ 500</td> </tr> </table>		Mechanical Data		Recommended Coupling Nut Torque	7.1 to 9.7 in-lbs	Coupling Proof Torque	15 in-lbs	Contact Captivation-axial	≥ 6.1 lbs	Durability (mating)	≥ 500								
Mechanical Data																			
Recommended Coupling Nut Torque	7.1 to 9.7 in-lbs																		
Coupling Proof Torque	15 in-lbs																		
Contact Captivation-axial	≥ 6.1 lbs																		
Durability (mating)	≥ 500																		
<table border="0"> <tr> <td colspan="2" data-bbox="129 1552 531 1603">Environmental Data</td> </tr> <tr> <td data-bbox="129 1610 794 1644">Temperature Range</td> <td data-bbox="794 1610 1482 1644">-55°C to +105°C</td> </tr> <tr> <td data-bbox="129 1659 794 1693">Thermal Shock</td> <td data-bbox="794 1659 1482 1693">MIL-STD-202, Method 107, Condition B</td> </tr> <tr> <td data-bbox="129 1709 794 1742">Moisture Resistance</td> <td data-bbox="794 1709 1482 1742">MIL-STD-202, Method 206</td> </tr> <tr> <td data-bbox="129 1758 794 1792">Corrosion</td> <td data-bbox="794 1758 1482 1792">MIL-STD-202, Method 101, Condition B</td> </tr> <tr> <td data-bbox="129 1807 794 1841">RoHS</td> <td data-bbox="794 1807 1482 1841">Compliant</td> </tr> </table>		Environmental Data		Temperature Range	-55°C to +105°C	Thermal Shock	MIL-STD-202, Method 107, Condition B	Moisture Resistance	MIL-STD-202, Method 206	Corrosion	MIL-STD-202, Method 101, Condition B	RoHS	Compliant						
Environmental Data																			
Temperature Range	-55°C to +105°C																		
Thermal Shock	MIL-STD-202, Method 107, Condition B																		
Moisture Resistance	MIL-STD-202, Method 206																		
Corrosion	MIL-STD-202, Method 101, Condition B																		
RoHS	Compliant																		

ADS-PC8PC8-1.15


Tr1 S11 Refl SWR RefLvl: 1 U Res: 50 mU/Div




Tr2 S12 Trans LogM RefLvl: 0 dB Res: 0.1 dB/Div



Tr3 S21 Trans LogM RefLvl: -0.5 dB Res: 0.1 dB/Div



Tr4 S22 Refl SWR RefLvl: 1 U Res: 50 mU/Div



Ch2 TR Start 50 MHz Stop 34.5 GHz IFBW 1 kHz Avg OFF Measuring State CORR