

ADS-PM8S8	<b>SMPM Jack To SMB Jack</b>	<b>50Ω</b>															
<p>Typical VSWR</p> <table border="1" style="margin-left: auto; margin-right: auto;"> <thead> <tr> <th>Part Number</th> <th>1~5Ghz</th> <th>6Ghz</th> </tr> </thead> <tbody> <tr> <td>AD-PM8S8</td> <td>1.07</td> <td>1.13</td> </tr> </tbody> </table>			Part Number	1~5Ghz	6Ghz	AD-PM8S8	1.07	1.13									
Part Number	1~5Ghz	6Ghz															
AD-PM8S8	1.07	1.13															
<p>NOTE: SMPM MATEABLE WITH GPPO™ (GILBERT ENGINEERING CO )</p>																	
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 20%;">Parts</th> <th style="width: 20%;">Material</th> <th style="width: 60%;">Plating (Micro-inch)</th> </tr> </thead> <tbody> <tr> <td>Contact Pin</td> <td>Beryllium Copper</td> <td>Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20</td> </tr> <tr> <td>Insulator</td> <td>Teflon</td> <td></td> </tr> <tr> <td>Body(Mini SMP)</td> <td>Beryllium Copper</td> <td>Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20</td> </tr> <tr> <td>Body(SMB)</td> <td>Stainless Steel</td> <td>Passivated</td> </tr> </tbody> </table>			Parts	Material	Plating (Micro-inch)	Contact Pin	Beryllium Copper	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20	Insulator	Teflon		Body(Mini SMP)	Beryllium Copper	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20	Body(SMB)	Stainless Steel	Passivated
Parts	Material	Plating (Micro-inch)															
Contact Pin	Beryllium Copper	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20															
Insulator	Teflon																
Body(Mini SMP)	Beryllium Copper	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20															
Body(SMB)	Stainless Steel	Passivated															
<p>Weight:</p>																	

This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.