



NO.	COMPONENTS	IMPEDANCE
1	BNC REVERSE POLARITY MALE	50 OHM
2	.085" TIN PLATED SEMI-RIGID CABLE (TIN PLATED RG405)	50 OHM
3	TNC FEMALE FOR BULKHEAD	50 OHM

BNC R/P MALE



TNC FEMALE  
FOR BULKHEAD


GASKET

7/16-28UNEF-2A  
1/2-28UNEF-2A

1.6 [.630] HEX  
1.75 [.689] HEX

L

JYE BAO P/N	L CM (INCH)
B60T85-85T-15	15 (5.906)
B60T85-85T-30	30 (11.811)
B60T85-85T-50	50 (19.685)
B60T85-85T-100	100 (39.370)
B60T85-85T-150	150 (59.055)
B60T85-85T-200	200 (78.740)
B60T85-85T-XXX	CUSTOM LENGTH IN CM



MOUNTING HOLE

LENGTH TOLERANCE  
IS ±1.5% OR ±10MM,  
WHICHEVER IS  
GREATER.

**JYE BAO CO., LTD.**  
TAIPEI TAIWAN

DESCRIPTION CABLE ASSEMBLY BNC R/P PLUG  
TO TNC JACK FOR BULKHEAD

JYE BAO DRAWING NO.  
B60T85-85T-XXX