



BMA8162-0142

**BMA Jack Crimp  $\phi 20\text{mm}$  2 Hole Flange**  
For RG142,RG400; 2.6GHz VSWR 1.2

50 $\Omega$



MOUNTING HOLE:



| Parts         | Material         | Plating (Micro-inch)                                   |
|---------------|------------------|--------------------------------------------------------|
| Ferrule       | Brass            | Tin-Zinc-Copper-Alloy 100 Over Copper 50               |
| Spring        | Stainless Steel  |                                                        |
| Barrel        | Brass            | Tin-Zinc-Copper-Alloy 100 Over Copper 50               |
| Contact Pin   | Beryllium Copper | Gold 4 Over Nickel-Phosphorous Alloy 80 Over Copper 20 |
| Insulator     | Teflon           |                                                        |
| Ferrule       | Brass            | Gold 4 Over Nickel-Phosphorous Alloy 80 Over Copper 20 |
| Contact Body  | Brass            | Tin-Zinc-Copper-Alloy 100 Over Copper 50               |
| Spring Washer | Beryllium Copper | Gold 4 Over Nickel-Phosphorous Alloy 80 Over Copper 20 |
| Spring Ring   | Beryllium Copper | Gold 4 Over Nickel-Phosphorous Alloy 80 Over Copper 20 |
| Body          | Brass            | Tin-Zinc-Copper-Alloy 100 Over Copper 50               |

Suitable Cables:RG142,RG400

This part number complies with RoHS.






Notice: JYEBAO reserves the right to make modifications deemed appropriate.

| BMA                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | BMA8162-0142                         |                   |                 |                     |                                      |                           |                         |                     |                                      |                       |           |                                    |       |                                    |       |                                                |            |                                |            |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|-------------------|-----------------|---------------------|--------------------------------------|---------------------------|-------------------------|---------------------|--------------------------------------|-----------------------|-----------|------------------------------------|-------|------------------------------------|-------|------------------------------------------------|------------|--------------------------------|------------|
| <div>Interface</div> MIL-STD-348B                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                                      |                   |                 |                     |                                      |                           |                         |                     |                                      |                       |           |                                    |       |                                    |       |                                                |            |                                |            |
| <div>Electrical Data</div> <table> <tr> <td>Impedance</td><td>50Ω</td></tr> <tr> <td>Frequency range</td><td>DC to 2.6GHz</td></tr> <tr> <td>VSWR</td><td>≤ 1.2 (DC to 2.6GHz)</td></tr> <tr> <td>Insertion loss</td><td>≤ 0.03 x √f(GHz) dB</td></tr> <tr> <td>Insulation resistance</td><td>≥ 5000MΩ</td></tr> <tr> <td>Contact resistance inner conductor</td><td>≤ 2mΩ</td></tr> <tr> <td>Contact resistance outer conductor</td><td>≤ 2mΩ</td></tr> <tr> <td>Dielectric withstanding voltage (at sea level)</td><td>1500 V rms</td></tr> <tr> <td>Working voltage (at sea level)</td><td>1000 V rms</td></tr> </table> |                                      | Impedance         | 50Ω             | Frequency range     | DC to 2.6GHz                         | VSWR                      | ≤ 1.2 (DC to 2.6GHz)    | Insertion loss      | ≤ 0.03 x √f(GHz) dB                  | Insulation resistance | ≥ 5000MΩ  | Contact resistance inner conductor | ≤ 2mΩ | Contact resistance outer conductor | ≤ 2mΩ | Dielectric withstanding voltage (at sea level) | 1500 V rms | Working voltage (at sea level) | 1000 V rms |
| Impedance                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 50Ω                                  |                   |                 |                     |                                      |                           |                         |                     |                                      |                       |           |                                    |       |                                    |       |                                                |            |                                |            |
| Frequency range                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | DC to 2.6GHz                         |                   |                 |                     |                                      |                           |                         |                     |                                      |                       |           |                                    |       |                                    |       |                                                |            |                                |            |
| VSWR                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | ≤ 1.2 (DC to 2.6GHz)                 |                   |                 |                     |                                      |                           |                         |                     |                                      |                       |           |                                    |       |                                    |       |                                                |            |                                |            |
| Insertion loss                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | ≤ 0.03 x √f(GHz) dB                  |                   |                 |                     |                                      |                           |                         |                     |                                      |                       |           |                                    |       |                                    |       |                                                |            |                                |            |
| Insulation resistance                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | ≥ 5000MΩ                             |                   |                 |                     |                                      |                           |                         |                     |                                      |                       |           |                                    |       |                                    |       |                                                |            |                                |            |
| Contact resistance inner conductor                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | ≤ 2mΩ                                |                   |                 |                     |                                      |                           |                         |                     |                                      |                       |           |                                    |       |                                    |       |                                                |            |                                |            |
| Contact resistance outer conductor                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | ≤ 2mΩ                                |                   |                 |                     |                                      |                           |                         |                     |                                      |                       |           |                                    |       |                                    |       |                                                |            |                                |            |
| Dielectric withstanding voltage (at sea level)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 1500 V rms                           |                   |                 |                     |                                      |                           |                         |                     |                                      |                       |           |                                    |       |                                    |       |                                                |            |                                |            |
| Working voltage (at sea level)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 1000 V rms                           |                   |                 |                     |                                      |                           |                         |                     |                                      |                       |           |                                    |       |                                    |       |                                                |            |                                |            |
| <div>Mechanical Data</div> <table> <tr> <td>Engagement force</td><td>≤ 3 lbs</td></tr> <tr> <td>Disengagement force</td><td>≤ 1.5 lbs</td></tr> <tr> <td>Contact captivation-axial</td><td>≥ 6.1 lbs</td></tr> <tr> <td>Durability (mating)</td><td>≥ 1000</td></tr> </table>                                                                                                                                                                                                                                                                                                                                               |                                      | Engagement force  | ≤ 3 lbs         | Disengagement force | ≤ 1.5 lbs                            | Contact captivation-axial | ≥ 6.1 lbs               | Durability (mating) | ≥ 1000                               |                       |           |                                    |       |                                    |       |                                                |            |                                |            |
| Engagement force                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | ≤ 3 lbs                              |                   |                 |                     |                                      |                           |                         |                     |                                      |                       |           |                                    |       |                                    |       |                                                |            |                                |            |
| Disengagement force                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | ≤ 1.5 lbs                            |                   |                 |                     |                                      |                           |                         |                     |                                      |                       |           |                                    |       |                                    |       |                                                |            |                                |            |
| Contact captivation-axial                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | ≥ 6.1 lbs                            |                   |                 |                     |                                      |                           |                         |                     |                                      |                       |           |                                    |       |                                    |       |                                                |            |                                |            |
| Durability (mating)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | ≥ 1000                               |                   |                 |                     |                                      |                           |                         |                     |                                      |                       |           |                                    |       |                                    |       |                                                |            |                                |            |
| <div>Environmental Data</div> <table> <tr> <td>Temperature range</td><td>-65°C to +165°C</td></tr> <tr> <td>Thermal shock</td><td>MIL-STD-202, Method 107, Condition B</td></tr> <tr> <td>Moisture resistance</td><td>MIL-STD-202, Method 106</td></tr> <tr> <td>Corrosion</td><td>MIL-STD-202, Method 101, Condition B</td></tr> <tr> <td>RoHS</td><td>Compliant</td></tr> </table>                                                                                                                                                                                                                                        |                                      | Temperature range | -65°C to +165°C | Thermal shock       | MIL-STD-202, Method 107, Condition B | Moisture resistance       | MIL-STD-202, Method 106 | Corrosion           | MIL-STD-202, Method 101, Condition B | RoHS                  | Compliant |                                    |       |                                    |       |                                                |            |                                |            |
| Temperature range                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | -65°C to +165°C                      |                   |                 |                     |                                      |                           |                         |                     |                                      |                       |           |                                    |       |                                    |       |                                                |            |                                |            |
| Thermal shock                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | MIL-STD-202, Method 107, Condition B |                   |                 |                     |                                      |                           |                         |                     |                                      |                       |           |                                    |       |                                    |       |                                                |            |                                |            |
| Moisture resistance                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | MIL-STD-202, Method 106              |                   |                 |                     |                                      |                           |                         |                     |                                      |                       |           |                                    |       |                                    |       |                                                |            |                                |            |
| Corrosion                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | MIL-STD-202, Method 101, Condition B |                   |                 |                     |                                      |                           |                         |                     |                                      |                       |           |                                    |       |                                    |       |                                                |            |                                |            |
| RoHS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Compliant                            |                   |                 |                     |                                      |                           |                         |                     |                                      |                       |           |                                    |       |                                    |       |                                                |            |                                |            |
| <div>Tooling</div> <table> <tr> <td>Crimping tool</td><td>CRT-1 or CRT-2</td></tr> <tr> <td>Crimp Insert</td><td>INSERT-B</td></tr> </table>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                      | Crimping tool     | CRT-1 or CRT-2  | Crimp Insert        | INSERT-B                             |                           |                         |                     |                                      |                       |           |                                    |       |                                    |       |                                                |            |                                |            |
| Crimping tool                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | CRT-1 or CRT-2                       |                   |                 |                     |                                      |                           |                         |                     |                                      |                       |           |                                    |       |                                    |       |                                                |            |                                |            |
| Crimp Insert                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | INSERT-B                             |                   |                 |                     |                                      |                           |                         |                     |                                      |                       |           |                                    |       |                                    |       |                                                |            |                                |            |

Notice: JYEBAO reserves the right to make modifications deemed appropriate.

# JYE BAO CO., LTD.

## CABLE ASSEMBLY INSTRUCTION

|                                                                                                                     |  |                                                                                                                     |            |         |   |
|---------------------------------------------------------------------------------------------------------------------|--|---------------------------------------------------------------------------------------------------------------------|------------|---------|---|
| BMA8162-0142                                                                                                        |  | DATE                                                                                                                | 2017/09/25 | REV     | — |
| <div>A</div>  <div>BODY</div>      |  | <div>B</div>  <div>FERRULE</div>  |            |         |   |
| DIAGRAM                                                                                                             |  | ASSEMBLY INSTRUCTION                                                                                                |            |         |   |
|                                   |  | Step 1: STRIP AS SHOWN.                                                                                             |            |         |   |
|                                  |  | Step 2: SLIDE FERRULE " B " OVER CABLE.<br>Step 3: SHARPEN CENTER CONDUCTOR TIP.                                    |            |         |   |
|                                  |  | Step 4: LOOSEN BRAIDING AND SLIDE CONNECTOR " A " IN PLACE.                                                         |            |         |   |
|                                  |  | Step 5: SLIDE FERRULE " B " TOWARDS THE CONNECTOR " A " AND CRIMP.<br>(USE 5.5mm/0.217inch HEX SECTION OF INSERT-B) |            |         |   |
| This part number complies with RoHS.<br>Notice: JYEBao reserves the right to make modifications deemed appropriate. |  |                                                                                                                     |            |         |   |
| APPROVED                                                                                                            |  | CHECKED                                                                                                             |            | DRAWING |   |
|                                                                                                                     |  |                                                                                                                     |            | Albert  |   |

# BMA8162-0142

S11

