


| NO. | COMPONENTS | IMPEDANCE |
|-----|--|-----------|
| 1 | MCX MALE | 50 OHM |
| 2 | .141" TIN PLATED SEMI-RIGID CABLE (TIN PLATED RG402) | 50 OHM |
| 3 | MMCX MALE RIGHT ANGLE | 50 OHM |

MCX MALE

MMCX MALE
RIGHT ANGLE



| JYE BAO P/N | L CM (INCH) |
|-----------------|------------------------|
| D30E39-141T-15 | 15 (5.906) |
| D30E39-141T-30 | 30 (11.811) |
| D30E39-141T-50 | 50 (19.685) |
| D30E39-141T-100 | 100 (39.370) |
| D30E39-141T-150 | 150 (59.055) |
| D30E39-141T-200 | 200 (78.740) |
| D30E39-141T-XXX | CUSTOM LENGTH IN CM |

| | |
|--|---|
| <p>LENGTH TOLERANCE IS $\pm 1.5\%$ OR $\pm 10\text{MM}$, WHICHEVER IS GREATER.</p> | <p>JYE BAO CO., LTD. TAIPEI TAIWAN</p> |
| | <p>DESCRIPTION CABLE ASSEMBLY MCX PLUG TO MMCX PLUG R/A</p> |
| | <p>JYE BAO DRAWING NO. D30E39-141T-XXX</p> |