


DCF-N3G2W0.1A100V2

2dB 50Ω N Plug/Jack DC Bias Passing Attenuator
3GHz VSWR 1.35 Rated 100V & 100mA

50Ω



Frequency Range: 100MHz-3GHz
Attenuation: 2dB
Attenuation accuracy: ± 2.5 dB
Impedance: 50ohm
VSWR 1.35 : 1 Max

Voltage Rating: 100V Max
DC Current: 100mA Max
RF Power (Average): 2W
Operating Temp Range: -50°C/+80°C

Parts	Material	Plating (Micro-inch)
Retainer Ring	Beryllium Copper	Tin-Zinc-Copper-Alloy 100 Over Copper 50
Gasket	Silicone	
Contact Pin	Beryllium Copper	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20
Insulator	Teflon	
Contact Body	Brass	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20
Body	Brass	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20
Coupling Nut	Brass	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20

This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.