

FATS-NM5NF5S6G2W30	30dB 50ohm Fixed Attenuator N Plug To N Jack 6GHz Rated 2W	50Ω																					
<p>Nominal impedance: 50Ω±0.25Ω over operating temperature range. Operating temperature range: -50 degrees Celcius to +80 degrees Celcius. VSWR deviation: ±0.1% over operating temperature range. Power rating: 2W over operating temperature range. Power rating (Peak): 100W for 25 Microseconds. Power coefficient: 0.001dB/W (change in attenuation with increase in power). Temperature coefficient: 0.001dB/Deg. C max., 0.0003dB/Deg. C type.</p>																							
<table border="1" style="border-collapse: collapse; width: 100%;"> <thead> <tr> <th rowspan="2">Attenuation</th> <th colspan="3">VSWR</th> <th colspan="3">Attenuation deviation (±dB)</th> </tr> <tr> <th>DC~2GHz</th> <th>2~5GHz</th> <th>5~6GHz</th> <th>DC~2GHz</th> <th>2~5GHz</th> <th>5~6GHz</th> </tr> </thead> <tbody> <tr> <td style="text-align: center;">30dB</td> <td style="text-align: center;">≤1.15</td> <td style="text-align: center;">≤1.25</td> <td style="text-align: center;">≤1.35</td> <td style="text-align: center;">±0.5dB</td> <td style="text-align: center;">±1.5dB</td> <td style="text-align: center;">±4dB</td> </tr> </tbody> </table>			Attenuation	VSWR			Attenuation deviation (±dB)			DC~2GHz	2~5GHz	5~6GHz	DC~2GHz	2~5GHz	5~6GHz	30dB	≤1.15	≤1.25	≤1.35	±0.5dB	±1.5dB	±4dB	
Attenuation	VSWR			Attenuation deviation (±dB)																			
	DC~2GHz	2~5GHz	5~6GHz	DC~2GHz	2~5GHz	5~6GHz																	
30dB	≤1.15	≤1.25	≤1.35	±0.5dB	±1.5dB	±4dB																	
<table border="1" style="border-collapse: collapse; width: 100%;"> <thead> <tr> <th style="width: 20%;">Parts</th> <th style="width: 20%;">Material</th> <th style="width: 60%;">Plating (Micro-inch)</th> </tr> </thead> <tbody> <tr> <td>Body</td> <td>Stainless Steel</td> <td>Passivated</td> </tr> <tr> <td>Retainer Ring</td> <td>Beryllium Copper</td> <td>Tin-Zinc-Copper-Alloy 100 Over Copper 50</td> </tr> <tr> <td>Insulator</td> <td>Teflon</td> <td></td> </tr> <tr> <td>Gasket</td> <td>Silicone</td> <td></td> </tr> <tr> <td>Contact Pin</td> <td>Beryllium Copper</td> <td>Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20</td> </tr> <tr> <td>Coupling Nut</td> <td>Stainless Steel</td> <td>Passivated</td> </tr> </tbody> </table>			Parts	Material	Plating (Micro-inch)	Body	Stainless Steel	Passivated	Retainer Ring	Beryllium Copper	Tin-Zinc-Copper-Alloy 100 Over Copper 50	Insulator	Teflon		Gasket	Silicone		Contact Pin	Beryllium Copper	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20	Coupling Nut	Stainless Steel	Passivated
Parts	Material	Plating (Micro-inch)																					
Body	Stainless Steel	Passivated																					
Retainer Ring	Beryllium Copper	Tin-Zinc-Copper-Alloy 100 Over Copper 50																					
Insulator	Teflon																						
Gasket	Silicone																						
Contact Pin	Beryllium Copper	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20																					
Coupling Nut	Stainless Steel	Passivated																					
weight: 47.75 g																							

This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.