


NO.	COMPONENTS	IMPEDANCE
1	K FEMALE	50 OHM
2	6003A	50 OHM
3	SLEEVE	

REVISION			
REV.	DESCRIPTION	DATE	APPROVED
-	INITIAL RELEASE	2021/04/22	



L CM (INCH)	L1 M (MM)
50 (19.685)	0.476 (475.5)
100 (39.370)	0.976 (975.5)
150 (59.055)	1.476 (1475.5)
200 (78.740)	1.976 (1975.5)
Custom length in CM	- - -

Spec	Phase stability vs bending ⁽¹⁾	Amplitude stability vs bending ⁽²⁾	Max VSWR	Max IL	Flexure life cycle ⁽³⁾
3GHz	±0.5° typ / ±1.0° max	±0.005dB typ / ±0.01dB max	1.12 : 1	≤ (0.0075dB/cm*Lcm)+0.15dB	≥ 20000
6GHz	±0.75° typ / ±1.5° max	±0.0075dB typ / ±0.015dB max	1.15 : 1	≤ (0.0115dB/cm*Lcm)+0.20dB	
12.4GHz	±1.0° typ / ±2.0° max	±0.01dB typ / ±0.02dB max	1.20 : 1	≤ (0.0185dB/cm*Lcm)+0.25dB	
18GHz	±1.5° typ / ±3.0° max	±0.015dB typ / ±0.03dB max	1.25 : 1	≤ (0.0230dB/cm*Lcm)+0.30dB	
26.5GHz	±2.0° typ / ±4.0° max	±0.020dB typ / ±0.04dB max	1.25 : 1	≤ (0.0285dB/cm*Lcm)+0.40dB	
40GHz	±3.0° typ / ±6.0° max	±0.030dB typ / ±0.06dB max	1.30 : 1	≤ (0.0390dB/cm*Lcm)+0.50dB	

Notes:

- Operating Temp.: -40°C / +85°C
- Static bend radius 18mm
- Dynamic bend radius 60mm
- RoHS Compliant

- Per IEC 60966-1, section 8.6, method 1
- Per IEC 60966-1, section 8.4
- Per IEC 60966-1, section 9.3

LENGTH TOLERANCE IS ±1.5% OR ±10MM, WHICHEVER IS GREATER.					STANDARD	REV	UNIT	JYE BAO CO., LTD. TAIPEI TAIWAN
					APPROVED	-	CM(INCH)	
					CHECKED		DATE	
					DRAWING		DATE	
3 600-SLEEVE SLEEVE 2 EA					DESCRIPTION CABLE ASSEMBLY K JACK TO K JACK			
2 6003A CABLE SEE TABLE L1 M					JYE BAO DRAWING NO.			
1 K8200S-6003 K JACK 2 EA					K80K80-63-40GXXX			
NO. PARTS NO. DESCRIPTION Q'TY U/M								

Albert