


NO.	COMPONENTS	IMPEDANCE
1	N MALE	50 OHM
2	.085" TIN PLATED SEMI-RIGID CABLE (TIN PLATED RG405)	50 OHM
3	BNC REVERSE POLARITY FEMALE FOR BULKHEAD	50 OHM

N MALE



1

2

BNC R/P FEMALE FOR BULKHEAD

GASKET

3


1/2-28UNEF-2A

1.6 [.630] HEX

1.75 [.689] HEX

L

JYE BAO P/N	L CM (INCH)
N30B95-85T-15	15 (5.906)
N30B95-85T-30	30 (11.811)
N30B95-85T-50	50 (19.685)
N30B95-85T-100	100 (39.370)
N30B95-85T-150	150 (59.055)
N30B95-85T-200	200 (78.740)
N30B95-85T-XXX	CUSTOM LENGTH IN CM



1.19
[.469]

1.29
[.508]

MOUNTING HOLE

<p>LENGTH TOLERANCE IS ±1.5% OR ±10MM, WHICHEVER IS GREATER.</p>	<p>JYE BAO CO., LTD.</p> <p>TAIPEI TAIWAN</p>
	<p>DESCRIPTION CABLE ASSEMBLY N PLUG TO BNC R/P JACK FOR BULKHEAD</p>
	<p>JYE BAO DRAWING NO. N30B95-85T-XXX</p>