



| NO. | COMPONENTS | IMPEDANCE |
|-----|---|-----------|
| 1 | N MALE RIGHT ANGLE | 50 OHM |
| 2 | .141" HANDBENDABLE CABLE (= JYEBAO P/N .141SRF-W-P-50) | 50 OHM |
| 3 | BNC REVERSE POLARITY FEMALE FOR BULKHEAD | 50 OHM |


N MALE
RIGHT ANGLE



BNC R/P FEMALE
FOR BULKHEAD



| JYE BAO P/N | L CM (INCH) |
|-----------------|------------------------|
| N39B95-141S-15 | 15 (5.906) |
| N39B95-141S-30 | 30 (11.811) |
| N39B95-141S-50 | 50 (19.685) |
| N39B95-141S-100 | 100 (39.370) |
| N39B95-141S-150 | 150 (59.055) |
| N39B95-141S-200 | 200 (78.740) |
| N39B95-141S-XXX | CUSTOM LENGTH IN CM |



MOUNTING HOLE

| | |
|--|---|
| <p>LENGTH TOLERANCE IS ±1.5% OR ±10MM, WHICHEVER IS GREATER.</p> | <p>JYE BAO CO., LTD.</p> <p>TAIPEI TAIWAN</p> |
| | <p>DESCRIPTION CABLE ASSEMBLY N PLUG R/A TO BNC R/P JACK FOR BULKHEAD</p> |
| | <p>JYE BAO DRAWING NO. N39B95-141S-XXX</p> |