


NO.	COMPONENTS	IMPEDANCE
1	N MALE RIGHT ANGLE	50 OHM
2	5002	50 OHM
3	ADHESIVE HEAT SHRINKING TUBE	
4	ADHESIVE HEAT SHRINKING TUBE	

REVISION			
REV.	DESCRIPTON	DATE	APPROVED
-	INITIAL RELEASE	2020/12/30	

TEST LEAD WITH EXTRA STURDY CABLE / CONNECTOR CONNECTION.



L CM (INCH)	L1 M (MM)
50 (19.685)	0.458 (458.0)
100 (39.370)	0.958 (958.0)
150 (59.055)	1.458 (1458.0)
200 (78.740)	1.958 (1958.0)
Custom length in CM	- - -

Spec	Phase stability vs bending ⁽¹⁾	Amplitude stability vs bending ⁽²⁾	Max VSWR	Max IL	Flexure life cycle ⁽³⁾
3GHz	±0.3° typ / ±0.5° max	±0.005dB typ / ±0.01dB max	1.12 : 1	≤ (0.0128dB/cm*Lcm)+0.15dB	≥ 10000
6GHz	±0.5° typ / ±0.75° max	±0.0075dB typ / ±0.015dB max	1.15 : 1	≤ (0.0189dB/cm*Lcm)+0.20dB	
12.4GHz	±0.75° typ / ±1.0° max	±0.010dB typ / ±0.02dB max	1.20 : 1	≤ (0.0293dB/cm*Lcm)+0.25dB	
18GHz	±1.0° typ / ±1.5° max	±0.015dB typ / ±0.03dB max	1.25 : 1	≤ (0.0361dB/cm*Lcm)+0.30dB	

Notes:

1. Operating Temp.: -55°C / +125°C
2. Static bend radius 5.1mm
3. Dynamic bend radius 30mm
4. RoHS Compliant

- (1) Per IEC 60966-1, section 8.6, method 1
- (2) Per IEC 60966-1, section 8.4
- (3) Per IEC 60966-1, section 9.3

				STANDARD		REV -	UNIT CM(INCH)	JYE BAO CO., LTD.	
				APPROVED				TAIPEI TAIWAN	
				CHECKED				DESCRIPTION CABLE ASSEMBLY N PLUG R/A TO N PLUG R/A	
				DRAWING				JYE BAO DRAWING NO. N39N39-5002-18GXXX	
4	AIS-15MM-BLACK	TUBE	0.10	M	LENGTH TOLERANCE IS ±1.5% OR ±10MM, WHICHEVER IS GREATER.			DATE	
3	AIS-6.4MM-BLACK	TUBE	0.05	M				DATE	
2	5002	CABLE	SEE TABLE L1	M				DATE	
1	N32SHS-M5002	N PLUG R/A	2	EA				DATE	
NO.	PARTS NO.	DESCRIPTION	Q'TY	U/M	<i>Albert</i>				DATE