


NO.	COMPONENTS	IMPEDANCE
1	SMP FEMALE	50 OHM
2	.085" HANDBENDABLE CABLE WITH FEP JACKET (=JYBAO P/N .085SRF-W-P-50-F)	50 OHM
3	HEAT SHRINKING TUBE	

REVISION			
REV.	DESCRIPTION	DATE	APPROVED
-	INITIAL RELEASE	2022/03/22	

SMP FEMALE

SMP FEMALE



JYE BAO P/N	Freq. (GHz)	Max. Return Loss	L CM (INCH)	L1 M (MM)
P80P80-85F-27GXXX	27	-16.5dB	50 (19.685)	0.494 (494.0)
			100 (39.370)	0.994 (994.0)
			150 (59.055)	1.494 (1494.0)
			200 (78.740)	1.994 (1994.0)
			CUSTOM LENGTH IN CM	- - -

				LENGTH TOLERANCE IS ±1.5% OR ±10MM, WHICHEVER IS GREATER.	STANDARD	REV -	UNIT CM(INCH)	JYE BAO CO., LTD. TAIPEI TAIWAN
					APPROVED	DATE		
					CHECKED	DATE		
					DRAWING	DATE		
3	G5(F)-4.0MM-BLACK	TUBE	0.02	M	<i>Albert</i>			DESCRIPTION
2	.085SRF-W-P-50-F	CABLE	SEE TABLE L1	M				CABLE ASSEMBLY SMP JACK TO SMP JACK
1	SMP8300-0085	SMP JACK	2	EA				JYE BAO DRAWING NO.
NO.	PARTS NO.	DESCRIPTION	Q'TY	U/M				P80P80-85F-27GXXX