


NO.	COMPONENTS	IMPEDANCE
1	SMP FEMALE	50 OHM
2	.085" HANDBENDABLE CABLE (= JYEBAO P/N .085SRF-W-P-50)	50 OHM

REVISION			
REV.	DESCRIPTION	DATE	APPROVED
-	INITIAL RELEASE	2022/03/22	

SMP FEMALE

SMP FEMALE



JYE BAO P/N	Freq. (GHz)	Max. Return Loss	L CM (INCH)	L1 M (MM)
P80P80-85S-18GXXX	18	-16.5dB	50 (19.685)	0.494 (494.0)
			100 (39.370)	0.994 (994.0)
			150 (59.055)	1.494 (1494.0)
			200 (78.740)	1.994 (1994.0)
			CUSTOM LENGTH IN CM	- - -

LENGTH TOLERANCE IS ±1.5% OR ±10MM, WHICHEVER IS GREATER.	STANDARD	REV -	UNIT CM(INCH)	JYE BAO CO., LTD. TAIPEI TAIWAN
	APPROVED		DATE	
	CHECKED		DATE	DESCRIPTION CABLE ASSEMBLY SMP JACK TO SMP JACK
	DRAWING <i>Albert</i>		DATE	JYE BAO DRAWING NO. P80P80-85S-18GXXX

2	.085SRF-W-P-50	CABLE	SEE TABLE L1	M
1	SMP8300-0085	SMP JACK	2	EA
NO.	PARTS NO.	DESCRIPTION	QTY	U/M