


NO.	COMPONENTS	IMPEDANCE
1	SMP FEMALE	50 OHM
2	.085" HANDBENDABLE CABLE WITH FEP JACKET (=JYBAO P/N .085SRF-W-P-50-F)	50 OHM
3	HEAT SHRINKING TUBE	
4	SMPM FEMALE	50 OHM

REVISION			
REV.	DESCRIPTION	DATE	APPROVED
-	INITIAL RELEASE	2022/04/12	

SMP FEMALE

SMPM FEMALE



JYE BAO P/N	Freq. (GHz)	Max. Return Loss	L CM (INCH)	L1 M (MM)
P80PM80-85F-18GXXX	18	-16.5dB	50 (19.685)	0.493 (492.5)
			100 (39.370)	0.993 (992.5)
			150 (59.055)	1.493 (1492.5)
			200 (78.740)	1.993 (1992.5)
			CUSTOM LENGTH IN CM	- - -

				STANDARD		REV -	UNIT CM(INCH)	JYE BAO CO., LTD.	
				APPROVED		DATE		TAIPEI TAIWAN	
				CHECKED		DATE		DESCRIPTION	
				DRAWING		DATE		CABLE ASSEMBLY SMP JACK TO SMPM JACK	
				Albert		DATE		JYE BAO DRAWING NO.	
						DATE		P80PM80-85F-18GXXX	
4	SMPM8300-0085	SMPM JACK	1	EA	LENGTH TOLERANCE IS ±1.5% OR ±10MM, WHICHEVER IS GREATER.				
3	G5(F)-4.0MM-BLACK	TUBE	0.03	M					
2	.085SRF-W-P-50-F	CABLE	SEE TABLE L1	M					
1	SMP8300-0085	SMP JACK	1	EA					
NO.	PARTS NO.	DESCRIPTION	QTY	U/M					