

PD-AF0.8/1G30W2W	SMA Jack To SMA Jack (Two Way) Power Divider		50Ω																		
<table border="1"> <thead> <tr> <th>Series</th> <th>Male / Female</th> <th>Frequency (GHz)</th> <th>Impedance (Ohm)</th> <th>Power (Watt)</th> <th>Ways</th> <th>Isolation (Min. dB)</th> <th>Return Loss</th> <th>Insertion Loss (typical)</th> </tr> </thead> <tbody> <tr> <td>SMA</td> <td>Female</td> <td>0.8 to 1GHz</td> <td>50Ω</td> <td>30W</td> <td>2 Ways</td> <td>22 dB</td> <td>≤-20dB</td> <td>3.5dB</td> </tr> </tbody> </table>	Series	Male / Female	Frequency (GHz)	Impedance (Ohm)	Power (Watt)	Ways	Isolation (Min. dB)	Return Loss	Insertion Loss (typical)	SMA	Female	0.8 to 1GHz	50Ω	30W	2 Ways	22 dB	≤-20dB	3.5dB			
Series	Male / Female	Frequency (GHz)	Impedance (Ohm)	Power (Watt)	Ways	Isolation (Min. dB)	Return Loss	Insertion Loss (typical)													
SMA	Female	0.8 to 1GHz	50Ω	30W	2 Ways	22 dB	≤-20dB	3.5dB													
<table border="1"> <thead> <tr> <th>Parts</th> <th>Material</th> </tr> </thead> <tbody> <tr> <td>SMA Jack</td> <td>Brass</td> </tr> <tr> <td>Housing</td> <td>Aluminum</td> </tr> </tbody> </table>	Parts	Material	SMA Jack	Brass	Housing	Aluminum															
Parts	Material																				
SMA Jack	Brass																				
Housing	Aluminum																				
Weight: 267 g																					

This part number complies with RoHS.
 Notice: JYEBAO reserves the right to make modifications deemed appropriate.