


NO.	COMPONENTS	IMPEDANCE
1	SMB MALE RIGHT ANGLE	50 OHM
2	.085" HANDBENDABLE CABLE (= JYBAO P/N .085SRF-W-P-50)	50 OHM
3	SMC FEMALE FOR BULKHEAD	50 OHM

SMB MALE
RIGHT ANGLE




2



L


SMC FEMALE
FOR BULKHEAD

3




NO.10-32UNF-2A
0.6 [L.236] HEX

0.435
[.171]



JYE BAO P/N	L CM (INCH)
S39MC85-85S-15	15 (5.906)
S39MC85-85S-30	30 (11.811)
S39MC85-85S-50	50 (19.685)
S39MC85-85S-100	100 (39.370)
S39MC85-85S-150	150 (59.055)
S39MC85-85S-200	200 (78.740)
S39MC85-85S-XXX	CUSTOM LENGTH IN CM



MOUNTING HOLE

<p>LENGTH TOLERANCE IS ±1.5% OR ±10MM, WHICHEVER IS GREATER.</p>	<p>JYE BAO CO., LTD.</p> <p>TAIPEI TAIWAN</p>	
	DESCRIPTION	CABLE ASSEMBLY SMB PLUG R/A TO SMC FEMALE FOR BULKHEAD
	JYE BAO DRAWING NO.	S39MC85-85S-XXX