

www.jyebao.com.tw

SMA Jack Low Profile 2 Hole End Launch SMA84LP-10/20 50Ω With $\phi 0.25$ mm (0.010inch) Launch Pin 18.89 12.7 [.744] [.500] 9.32 6.35 [.367] [.250] 2-LOCK_ WASHER 2.55 [.100] 2-M2X0.4P-1/4-36UNS-2A 9.53 4.24 GROUNDING TRANSITION [.167] [.188] [.250] PLATE 9.5 SQ. [.374 SQ.] THREADED_ [.375] CLAMPING PLATE CIRCUIT TRACE Ø1.61 1.27 [ø.063] Ø0.5 [ø.020] Ø0.25 [Ø.010] LAUNCH PIN-EQ. EQ. SUBSTRATE VIEW A **DETAIL B** [.375] SUBSTRATE GROUND CONDUCTOR NOTE: LOW VSWR; DIRECT MATCH TO SOUTHWEST MICROWAVE P/N 292-04A-6

		_
Parts	Material	Plating (Micro-inch)
Washer	Stainless Steel	Passivated
Screw	Stainless Steel	Passivated
Contact Pin	Beryllium Copper	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20
Insulator	Teflon	
Clamping Plate	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50
Grounding Plate	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50
Transition Block	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50
Body	Stainless Steel	Passivated
	1	<u>'</u>

Notice: JYEBAO reserves the right to make modifications deemed appropriate.