



This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.



SMA		SMA8F26E-0018
Interface		
MIL-STD-348B		
Mechanically compatible wit	h	2.92 & 3.5
Electrical Data		
Impedance		50Ω
Frequency range		DC to 27GHz
VSWR		$\leq 1.2$ (DC to 27GHz)
Insertion loss		$\leq 0.04 \text{ x} \sqrt{f(GHz)} dB$
Insulation resistance		$\geq$ 5000M $\Omega$
Contact resistance inner conductor		$\leq 3m\Omega$
Contact resistance outer conductor		≤2mΩ
Dielectric withstanding voltage (at sea level)		1500 V rms
Working voltage (at sea leve	el)	500 V rms
Mechanical Data		
Recommended coupling nut torque		7 to 9.5 inch lbs
Coupling proof torque		15 inch lbs
Coupling nut retention force		$\geq$ 60.7 lbs
Contact Captivation-axial		$\geq$ 6.1 lbs
Durability (mating)		≧500
Environmental Data		
Temperature range		-40°C to +125°C
Thermal shock		MIL-STD-202, Method 107, Condition B
Moisture resistance		MIL-STD-202, Method 106
Corrosion		MIL-STD-202, Method 101, Condition B
RoHS		Compliant
Tooling		

Notice: JYEBAO reserves the right to make modifications deemed appropriate.