

SMB8475-SH00	SMB Jack PCB Mount With Round Contact (Φ0.51); 2GHz VSWR 1.25	75Ω												
<p style="text-align: center;">MOUNTING HOLE:</p> <p style="text-align: center;"> Pattern and signal are on the same side Thickness of PCB: 1.6mm The material of PCB: Er=4.8 </p>														
NOTE: MINI SMB 75 OHM INTERFACE														
<table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th style="width: 20%;">Parts</th> <th style="width: 20%;">Material</th> <th style="width: 60%;">Plating (Micro-inch)</th> </tr> </thead> <tbody> <tr> <td>Contact Pin</td> <td>Beryllium Copper</td> <td>Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20</td> </tr> <tr> <td>Insulator</td> <td>Teflon</td> <td></td> </tr> <tr> <td>Body</td> <td>Brass</td> <td>Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20</td> </tr> </tbody> </table>			Parts	Material	Plating (Micro-inch)	Contact Pin	Beryllium Copper	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20	Insulator	Teflon		Body	Brass	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20
Parts	Material	Plating (Micro-inch)												
Contact Pin	Beryllium Copper	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20												
Insulator	Teflon													
Body	Brass	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20												

This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.

SMB	SMB8475-SH00																				
<table border="0"> <tr> <td colspan="2" data-bbox="167 344 568 389">Electrical Data</td> </tr> <tr> <td data-bbox="167 405 837 439">Impedance</td> <td data-bbox="853 405 1436 439">75Ω</td> </tr> <tr> <td data-bbox="167 454 837 488">Frequency range</td> <td data-bbox="853 454 1436 488">DC to 2GHz</td> </tr> <tr> <td data-bbox="167 504 837 537">VSWR</td> <td data-bbox="853 504 1436 537">≤ 1.25 (DC to 2GHz)</td> </tr> <tr> <td data-bbox="167 553 837 586">Insertion loss</td> <td data-bbox="853 553 1436 586">≤ 0.1 x √f(GHz)dB</td> </tr> <tr> <td data-bbox="167 602 837 636">Insulation resistance</td> <td data-bbox="853 602 1436 636">≥ 10000MΩ</td> </tr> <tr> <td data-bbox="167 651 837 685">Contact resistance inner conductor</td> <td data-bbox="853 651 1436 685">≤ 5mΩ</td> </tr> <tr> <td data-bbox="167 701 837 734">Contact resistance outer conductor</td> <td data-bbox="853 701 1436 734">≤ 2.5mΩ</td> </tr> <tr> <td data-bbox="167 750 837 784">Dielectric withstanding voltage (at sea level)</td> <td data-bbox="853 750 1436 784">750 V rms</td> </tr> <tr> <td data-bbox="167 799 837 833">Working voltage (at sea level)</td> <td data-bbox="853 799 1436 833">250 V rms</td> </tr> </table>		Electrical Data		Impedance	75Ω	Frequency range	DC to 2GHz	VSWR	≤ 1.25 (DC to 2GHz)	Insertion loss	≤ 0.1 x √f(GHz)dB	Insulation resistance	≥ 10000MΩ	Contact resistance inner conductor	≤ 5mΩ	Contact resistance outer conductor	≤ 2.5mΩ	Dielectric withstanding voltage (at sea level)	750 V rms	Working voltage (at sea level)	250 V rms
Electrical Data																					
Impedance	75Ω																				
Frequency range	DC to 2GHz																				
VSWR	≤ 1.25 (DC to 2GHz)																				
Insertion loss	≤ 0.1 x √f(GHz)dB																				
Insulation resistance	≥ 10000MΩ																				
Contact resistance inner conductor	≤ 5mΩ																				
Contact resistance outer conductor	≤ 2.5mΩ																				
Dielectric withstanding voltage (at sea level)	750 V rms																				
Working voltage (at sea level)	250 V rms																				
<table border="0"> <tr> <td colspan="2" data-bbox="167 936 568 981">Mechanical Data</td> </tr> <tr> <td data-bbox="167 996 837 1030">Disengagement force</td> <td data-bbox="853 996 1436 1030">1.8 to 14.2 lbs</td> </tr> <tr> <td data-bbox="167 1046 837 1079">Engagement force</td> <td data-bbox="853 1046 1436 1079">1.8 to 14.2 lbs</td> </tr> <tr> <td data-bbox="167 1095 837 1128">Contact captivation-axial</td> <td data-bbox="853 1095 1436 1128">≥ 4 lbs</td> </tr> <tr> <td data-bbox="167 1144 837 1178">Durability (mating)</td> <td data-bbox="853 1144 1436 1178">≥ 500</td> </tr> </table>		Mechanical Data		Disengagement force	1.8 to 14.2 lbs	Engagement force	1.8 to 14.2 lbs	Contact captivation-axial	≥ 4 lbs	Durability (mating)	≥ 500										
Mechanical Data																					
Disengagement force	1.8 to 14.2 lbs																				
Engagement force	1.8 to 14.2 lbs																				
Contact captivation-axial	≥ 4 lbs																				
Durability (mating)	≥ 500																				
<table border="0"> <tr> <td colspan="2" data-bbox="167 1290 568 1335">Environmental Data</td> </tr> <tr> <td data-bbox="167 1350 837 1384">Temperature range</td> <td data-bbox="853 1350 1436 1384">-65°C to +165°C</td> </tr> <tr> <td data-bbox="167 1400 837 1433">Thermal shock</td> <td data-bbox="853 1400 1436 1433">MIL-STD-202, Method 107, Condition B</td> </tr> <tr> <td data-bbox="167 1449 837 1482">Moisture resistance</td> <td data-bbox="853 1449 1436 1482">MIL-STD-202, Method 106</td> </tr> <tr> <td data-bbox="167 1498 837 1532">Corrosion</td> <td data-bbox="853 1498 1436 1532">MIL-STD-202, Method 101, Condition B</td> </tr> <tr> <td data-bbox="167 1547 837 1581">RoHS</td> <td data-bbox="853 1547 1436 1581">Compliant</td> </tr> </table>		Environmental Data		Temperature range	-65°C to +165°C	Thermal shock	MIL-STD-202, Method 107, Condition B	Moisture resistance	MIL-STD-202, Method 106	Corrosion	MIL-STD-202, Method 101, Condition B	RoHS	Compliant								
Environmental Data																					
Temperature range	-65°C to +165°C																				
Thermal shock	MIL-STD-202, Method 107, Condition B																				
Moisture resistance	MIL-STD-202, Method 106																				
Corrosion	MIL-STD-202, Method 101, Condition B																				
RoHS	Compliant																				
<table border="0"> <tr> <td colspan="2" data-bbox="167 1644 568 1688">Tooling</td> </tr> </table>		Tooling																			
Tooling																					

Notice: JYEBAO reserves the right to make modifications deemed appropriate.

SMB8475-SH00

S11

