

SMP3F26A-SB12	SMP Plug Field Replaceable For Panel Receptacle	50Ω															
<p style="text-align: right;">Accepts Ø0.3mm (Ø.012inch) Pin Size</p>																	
<p>Note: Smooth Bore.</p>																	
<table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr> <th style="width: 20%;">Parts</th> <th style="width: 20%;">Material</th> <th style="width: 60%;">Plating (Micro-inch)</th> </tr> </thead> <tbody> <tr> <td>Insulator</td> <td>Teflon</td> <td></td> </tr> <tr> <td>Contact Pin</td> <td>Beryllium Copper</td> <td>Gold 4 Over Nickel Phosphorous Alloy 80 Over Copper 20</td> </tr> <tr> <td>Ferrule</td> <td>Stainless Steel</td> <td>Passivated</td> </tr> <tr> <td>Body</td> <td>Stainless Steel</td> <td>Passivated</td> </tr> </tbody> </table>			Parts	Material	Plating (Micro-inch)	Insulator	Teflon		Contact Pin	Beryllium Copper	Gold 4 Over Nickel Phosphorous Alloy 80 Over Copper 20	Ferrule	Stainless Steel	Passivated	Body	Stainless Steel	Passivated
Parts	Material	Plating (Micro-inch)															
Insulator	Teflon																
Contact Pin	Beryllium Copper	Gold 4 Over Nickel Phosphorous Alloy 80 Over Copper 20															
Ferrule	Stainless Steel	Passivated															
Body	Stainless Steel	Passivated															
<p>Weight:</p>																	

This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.