



TNC8105T-L100

**TNC Isolated Jack Crimp Bulkhead**  
For JBY100,LMR100; 1GHz VSWR 1.2

**50Ω**



**MOUNTING HOLE**



| Parts      | Material        | Plating (Micro-inch)                                   |
|------------|-----------------|--------------------------------------------------------|
| Ferrule    | Brass           | Tin-Zinc-Copper-Alloy 100 Over Copper 50               |
| Center Pin | Phosphor Bronze | Gold 4 Over Nickel Phosphorous Alloy 80 Over Copper 20 |
| Hex Nut    | Brass           | Tin-Zinc-Copper-Alloy 100 Over Copper 50               |
| Washer     | Brass           | Tin-Zinc-Copper-Alloy 100 Over Copper 50               |
| Solder Tag | Brass           | Tin-Zinc-Copper-Alloy 100 Over Copper 50               |
| Barrel     | Brass           | Tin-Zinc-Copper-Alloy 100 Over Copper 50               |
| Insulator  | Teflon          |                                                        |
| Body       | Brass           | Tin-Zinc-Copper-Alloy 100 Over Copper 50               |

Weight: 14.82g

Suitable Cables:JBY100

**This part number complies with RoHS.**









**Notice: JYEBAO reserves the right to make modifications deemed appropriate.**

| TNC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | TNC8105T-L100                             |                                 |                     |                       |                                      |                           |                         |                     |                                           |                       |                           |                                    |                          |                                    |                        |                                                |            |                                |           |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------|---------------------------------|---------------------|-----------------------|--------------------------------------|---------------------------|-------------------------|---------------------|-------------------------------------------|-----------------------|---------------------------|------------------------------------|--------------------------|------------------------------------|------------------------|------------------------------------------------|------------|--------------------------------|-----------|
| <div>Interface</div> MIL-STD-348B                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                           |                                 |                     |                       |                                      |                           |                         |                     |                                           |                       |                           |                                    |                          |                                    |                        |                                                |            |                                |           |
| <div>Electrical Data</div> <table> <tr> <td>Impedance</td><td>50Ω</td></tr> <tr> <td>Frequency range</td><td>DC to 1GHz</td></tr> <tr> <td>VSWR</td><td><math>\leq 1.2</math> (DC to 1GHz)</td></tr> <tr> <td>Insertion loss</td><td><math>\leq 0.1 \times \sqrt{f(\text{GHz})}</math> dB</td></tr> <tr> <td>Insulation resistance</td><td><math>\geq 5000\text{M}\Omega</math></td></tr> <tr> <td>Contact resistance inner conductor</td><td><math>\leq 1.5\text{m}\Omega</math></td></tr> <tr> <td>Contact resistance outer conductor</td><td><math>\leq 1\text{m}\Omega</math></td></tr> <tr> <td>Dielectric withstanding voltage (at sea level)</td><td>1500 V rms</td></tr> <tr> <td>Working voltage (at sea level)</td><td>500 V rms</td></tr> </table> |                                           | Impedance                       | 50Ω                 | Frequency range       | DC to 1GHz                           | VSWR                      | $\leq 1.2$ (DC to 1GHz) | Insertion loss      | $\leq 0.1 \times \sqrt{f(\text{GHz})}$ dB | Insulation resistance | $\geq 5000\text{M}\Omega$ | Contact resistance inner conductor | $\leq 1.5\text{m}\Omega$ | Contact resistance outer conductor | $\leq 1\text{m}\Omega$ | Dielectric withstanding voltage (at sea level) | 1500 V rms | Working voltage (at sea level) | 500 V rms |
| Impedance                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 50Ω                                       |                                 |                     |                       |                                      |                           |                         |                     |                                           |                       |                           |                                    |                          |                                    |                        |                                                |            |                                |           |
| Frequency range                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | DC to 1GHz                                |                                 |                     |                       |                                      |                           |                         |                     |                                           |                       |                           |                                    |                          |                                    |                        |                                                |            |                                |           |
| VSWR                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | $\leq 1.2$ (DC to 1GHz)                   |                                 |                     |                       |                                      |                           |                         |                     |                                           |                       |                           |                                    |                          |                                    |                        |                                                |            |                                |           |
| Insertion loss                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | $\leq 0.1 \times \sqrt{f(\text{GHz})}$ dB |                                 |                     |                       |                                      |                           |                         |                     |                                           |                       |                           |                                    |                          |                                    |                        |                                                |            |                                |           |
| Insulation resistance                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | $\geq 5000\text{M}\Omega$                 |                                 |                     |                       |                                      |                           |                         |                     |                                           |                       |                           |                                    |                          |                                    |                        |                                                |            |                                |           |
| Contact resistance inner conductor                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | $\leq 1.5\text{m}\Omega$                  |                                 |                     |                       |                                      |                           |                         |                     |                                           |                       |                           |                                    |                          |                                    |                        |                                                |            |                                |           |
| Contact resistance outer conductor                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | $\leq 1\text{m}\Omega$                    |                                 |                     |                       |                                      |                           |                         |                     |                                           |                       |                           |                                    |                          |                                    |                        |                                                |            |                                |           |
| Dielectric withstanding voltage (at sea level)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 1500 V rms                                |                                 |                     |                       |                                      |                           |                         |                     |                                           |                       |                           |                                    |                          |                                    |                        |                                                |            |                                |           |
| Working voltage (at sea level)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | 500 V rms                                 |                                 |                     |                       |                                      |                           |                         |                     |                                           |                       |                           |                                    |                          |                                    |                        |                                                |            |                                |           |
| <div>Mechanical Data</div> <table> <tr> <td>Recommended coupling nut torque</td><td>4.1 to 6.1 inch lbs</td></tr> <tr> <td>Coupling proof torque</td><td>15 inch lbs</td></tr> <tr> <td>Contact captivation-axial</td><td><math>\geq 6.1</math> lbs</td></tr> <tr> <td>Durability (mating)</td><td><math>\geq 500</math></td></tr> </table>                                                                                                                                                                                                                                                                                                                                                                                                                   |                                           | Recommended coupling nut torque | 4.1 to 6.1 inch lbs | Coupling proof torque | 15 inch lbs                          | Contact captivation-axial | $\geq 6.1$ lbs          | Durability (mating) | $\geq 500$                                |                       |                           |                                    |                          |                                    |                        |                                                |            |                                |           |
| Recommended coupling nut torque                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 4.1 to 6.1 inch lbs                       |                                 |                     |                       |                                      |                           |                         |                     |                                           |                       |                           |                                    |                          |                                    |                        |                                                |            |                                |           |
| Coupling proof torque                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 15 inch lbs                               |                                 |                     |                       |                                      |                           |                         |                     |                                           |                       |                           |                                    |                          |                                    |                        |                                                |            |                                |           |
| Contact captivation-axial                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | $\geq 6.1$ lbs                            |                                 |                     |                       |                                      |                           |                         |                     |                                           |                       |                           |                                    |                          |                                    |                        |                                                |            |                                |           |
| Durability (mating)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | $\geq 500$                                |                                 |                     |                       |                                      |                           |                         |                     |                                           |                       |                           |                                    |                          |                                    |                        |                                                |            |                                |           |
| <div>Environmental Data</div> <table> <tr> <td>Temperature range</td><td>-65°C to +165°C</td></tr> <tr> <td>Thermal shock</td><td>MIL-STD-202, Method 107, Condition B</td></tr> <tr> <td>Moisture resistance</td><td>MIL-STD-202, Method 106</td></tr> <tr> <td>Corrosion</td><td>MIL-STD-202, Method 101, Condition B</td></tr> <tr> <td>RoHS</td><td>Compliant</td></tr> </table>                                                                                                                                                                                                                                                                                                                                                                          |                                           | Temperature range               | -65°C to +165°C     | Thermal shock         | MIL-STD-202, Method 107, Condition B | Moisture resistance       | MIL-STD-202, Method 106 | Corrosion           | MIL-STD-202, Method 101, Condition B      | RoHS                  | Compliant                 |                                    |                          |                                    |                        |                                                |            |                                |           |
| Temperature range                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | -65°C to +165°C                           |                                 |                     |                       |                                      |                           |                         |                     |                                           |                       |                           |                                    |                          |                                    |                        |                                                |            |                                |           |
| Thermal shock                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | MIL-STD-202, Method 107, Condition B      |                                 |                     |                       |                                      |                           |                         |                     |                                           |                       |                           |                                    |                          |                                    |                        |                                                |            |                                |           |
| Moisture resistance                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | MIL-STD-202, Method 106                   |                                 |                     |                       |                                      |                           |                         |                     |                                           |                       |                           |                                    |                          |                                    |                        |                                                |            |                                |           |
| Corrosion                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | MIL-STD-202, Method 101, Condition B      |                                 |                     |                       |                                      |                           |                         |                     |                                           |                       |                           |                                    |                          |                                    |                        |                                                |            |                                |           |
| RoHS                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Compliant                                 |                                 |                     |                       |                                      |                           |                         |                     |                                           |                       |                           |                                    |                          |                                    |                        |                                                |            |                                |           |
| <div>Tooling</div> <table> <tr> <td>Crimping tool</td><td>CRT-1 or CRT-2</td></tr> <tr> <td>Crimp insert</td><td>INSERT-D</td></tr> </table>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                                           | Crimping tool                   | CRT-1 or CRT-2      | Crimp insert          | INSERT-D                             |                           |                         |                     |                                           |                       |                           |                                    |                          |                                    |                        |                                                |            |                                |           |
| Crimping tool                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | CRT-1 or CRT-2                            |                                 |                     |                       |                                      |                           |                         |                     |                                           |                       |                           |                                    |                          |                                    |                        |                                                |            |                                |           |
| Crimp insert                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | INSERT-D                                  |                                 |                     |                       |                                      |                           |                         |                     |                                           |                       |                           |                                    |                          |                                    |                        |                                                |            |                                |           |

Notice: JYEBAO reserves the right to make modifications deemed appropriate.

# JYE BAO CO., LTD.

## CABLE ASSEMBLY INSTRUCTION

|                                                                                                                     |  |                                                                                                                                                                                                                                                  |                                                                                                  |                                                                                                  |   |
|---------------------------------------------------------------------------------------------------------------------|--|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|---|
| TNC8105T-L100                                                                                                       |  | DATE                                                                                                                                                                                                                                             | 2016/02/15                                                                                       | REV                                                                                              | — |
| <div>A</div>                       |  | <div>B</div>                                                                                                                                                    | <div>C</div>  | <div>D</div>  |   |
| BODY + SOLDER TAG<br>+ WASHER + HEX NUT                                                                             |  | CONTACT PIN                                                                                                                                                                                                                                      | INSULATOR                                                                                        | FERRULE                                                                                          |   |
| DIAGRAM                                                                                                             |  | ASSEMBLY INSTRUCTION                                                                                                                                                                                                                             |                                                                                                  |                                                                                                  |   |
|                                   |  | Step 1: STRIP AS SHOWN.                                                                                                                                                                                                                          |                                                                                                  |                                                                                                  |   |
|                                  |  | Step 2: SLIDE FERRULE " D " OVER CABLE.<br>Step 3: LOOSEN BRAIDING AND SLIDE INSULATOR " C " IN PLACE.<br>Step 4: PUT PIN " B " ON CENTER CONDUCTOR AND SOLDER OR CRIMP IN " Y ".<br>(USE SQUARE 1.6mm/0.063inch SECTION OF INSERT-D IF CRIMPED) |                                                                                                  |                                                                                                  |   |
|                                  |  | Step 5: SLIDE CONNECTOR " A " IN PLACE.                                                                                                                                                                                                          |                                                                                                  |                                                                                                  |   |
|                                  |  | Step 6: SLIDE FERRULE " D " TOWARDS THE CONNECTOR " A " AND CRIMP.<br>(USE 4.5mm/0.177inch HEX SECTION OF INSERT-D)                                                                                                                              |                                                                                                  |                                                                                                  |   |
| This part number complies with RoHS.<br>Notice: JYEBAO reserves the right to make modifications deemed appropriate. |  |                                                                                                                                                                                                                                                  |                                                                                                  |                                                                                                  |   |
| APPROVED                                                                                                            |  | CHECKED                                                                                                                                                                                                                                          |                                                                                                  | DRAWING                                                                                          |   |
|                                                                                                                     |  |                                                                                                                                                                                                                                                  |                                                                                                  | Albert                                                                                           |   |

# TNC8105T-L100

