

<b>TWINAX COAXIAL CABLE</b>	<b>TWINAX-5001</b>
<b>DIMENSIONS</b>	
Center Conductor: stranded	16*24
Dielectric Diameter (one black & one red)	
(inch)	0.071
(mm)	1.8
Diameter over Outer Braid	
(inch)	0.177
(mm)	4.5
Jacket Diameter	
(inch)	0.24
(mm)	6.1
<b>MATERIAL SPECIFICATIONS</b>	
Jacket	PVC
Outer Braid	Tin Plated Copper
Inner Braid	Cotton Braid
Dielectric Center Conductor (two)	Polyethylene
Center Conductor (two)	Tin Plated Copper
<b>ELECTRICAL CHARACTERISTICS</b>	
Capacitance Between Conductors	
(pF/ft)	18
(pF/m)	59
Capacitance between one conductor and other conductors connected to shield	
(pF/ft)	32
(pF/m)	105
Maximum Working Voltage	1000
Shield Coverage (%)	85
<b>MECHANICAL CHARACTERISTICS</b>	
Max. Operating Temperature (°C)	-40/+80
Min. Bend Radius	
(inch)	1.378
(mm)	35
Weight	
(g/Ft)	15.24
(g/M)	50

This part number complies with RoHS.

Notice: JYEBAO reserves the right to make modifications deemed appropriate.