


UHF3200-0214

UHF Plug Clamp For RG214
300MHz VSWR 1.2



Parts	Material	Plating(Micro-inch)
Contact Pin	Brass	Gold 4 Over Nickel-Phosphorus Alloy 80 Over Copper 20
Insulator	Teflon	
Body	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50
Coupling Nut	Brass	Tin-Zinc-Copper-Alloy 100 Over Copper 50

Weight: 21.63 g
Suitable Cables: RG214

This part number complies with RoHS.






Notice: JYEBAO reserves the right to make modifications deemed appropriate.

UHF	UHF3200-0214																		
Interface IEC 60169-12																			
Electrical Data <table> <tr> <td>Impedance</td><td>Non constant</td></tr> <tr> <td>Frequency range</td><td>300MHz</td></tr> <tr> <td>VSWR</td><td>≤ 1.2 (DC to 300MHz)</td></tr> <tr> <td>Insulation resistance</td><td>$\geq 5000M\Omega$</td></tr> <tr> <td>Contact resistance inner conductor</td><td>$\leq 5m\Omega$</td></tr> <tr> <td>Contact resistance outer conductor</td><td>$\leq 3m\Omega$</td></tr> <tr> <td>Dielectric withstanding voltage (at sea level)</td><td>2000 V rms</td></tr> <tr> <td>Working Voltage (at sea level)</td><td>750 V rms</td></tr> <tr> <td>Power Handling</td><td>400W (300MHz)</td></tr> </table>		Impedance	Non constant	Frequency range	300MHz	VSWR	≤ 1.2 (DC to 300MHz)	Insulation resistance	$\geq 5000M\Omega$	Contact resistance inner conductor	$\leq 5m\Omega$	Contact resistance outer conductor	$\leq 3m\Omega$	Dielectric withstanding voltage (at sea level)	2000 V rms	Working Voltage (at sea level)	750 V rms	Power Handling	400W (300MHz)
Impedance	Non constant																		
Frequency range	300MHz																		
VSWR	≤ 1.2 (DC to 300MHz)																		
Insulation resistance	$\geq 5000M\Omega$																		
Contact resistance inner conductor	$\leq 5m\Omega$																		
Contact resistance outer conductor	$\leq 3m\Omega$																		
Dielectric withstanding voltage (at sea level)	2000 V rms																		
Working Voltage (at sea level)	750 V rms																		
Power Handling	400W (300MHz)																		
Environmental Data <table> <tr> <td>Temperature range</td><td>-65°C to +165°C</td></tr> <tr> <td>Thermal shock</td><td>MIL-STD-202, Method 107, Condition B</td></tr> <tr> <td>Moisture resistance</td><td>MIL-STD-202, Method 106</td></tr> <tr> <td>Corrosion</td><td>MIL-STD-202, Method 101, Condition B</td></tr> <tr> <td>RoHS</td><td></td></tr> </table>		Temperature range	-65°C to +165°C	Thermal shock	MIL-STD-202, Method 107, Condition B	Moisture resistance	MIL-STD-202, Method 106	Corrosion	MIL-STD-202, Method 101, Condition B	RoHS									
Temperature range	-65°C to +165°C																		
Thermal shock	MIL-STD-202, Method 107, Condition B																		
Moisture resistance	MIL-STD-202, Method 106																		
Corrosion	MIL-STD-202, Method 101, Condition B																		
RoHS																			
Tooling																			

Notice: JYEBAO reserves the right to make modifications deemed appropriate.

JYE BAO CO., LTD.

CABLE ASSEMBLY INSTRUCTION

UHF3200-0214		DATE	2017/09/25	REV	—
A		B			
					
BODY + CONTACT PIN		SHELL			
DIAGRAM		ASSEMBLY INSTRUCTION			
		Step 1: STRIP AS SHOWN.			
		Step 2: SLIDE SHELL " B " OVER CABLE.			
		Step 3: PUT PREPARED CABLE INTO BODY " A " AND SOLDER IN " X " AND IN " Y " .			
		Step 4: FINALLY SCREW SHELL " B " ON THE CONNECTOR BODY " A " .			
This part number complies with RoHS. Notice: JYEBAO reserves the right to make modifications deemed appropriate.					
APPROVED		CHECKED		DRAWING	
				<i>Albert</i>	